

Title (en)
CONNECTING DEVICE FOR SUSPENDED STRUCTURES

Publication
EP 0173359 B1 19891018 (FR)

Application
EP 85200973 A 19850619

Priority
BE 2060485 A 19840829

Abstract (en)
[origin: EP0173359A2] The coupling member (1) is intended for securing the carrier members (4) of a suspended ceiling. It comprises two downwardly extending portions (2,3) connected at their upper ends via a horizontal portion (5), with a central upwardly extending U-section portion (6) provided with vertically spaced bores for securing to a hanger. The underside of the horizontal portion (5) is provided with lips (10) near its ends capable of engaging the upper ends (11) of the members such that these members are located to prevent their rotational movement due to off-centre load (P). Further faces (14,15;16,17) may be provided for locating the sides (19) of the cable ducts (20).

IPC 1-7
E04B 5/55; E04B 5/58

IPC 8 full level
E04B 9/14 (2006.01); **E04B 9/18** (2006.01)

CPC (source: EP)
E04B 9/14 (2013.01); **E04B 9/18** (2013.01)

Cited by
US8615947B2; WO2013184372A1

Designated contracting state (EPC)
DE FR GB

DOCDB simple family (publication)
EP 0173359 A2 19860305; EP 0173359 A3 19870826; EP 0173359 B1 19891018

DOCDB simple family (application)
EP 85200973 A 19850619