

Title (en)  
METHOD AND DEVICE FOR MAKING A YARN

Publication  
**EP 0178466 B1 19891220 (DE)**

Application  
**EP 85111626 A 19850913**

Priority  
CH 492484 A 19841015

Abstract (en)  
[origin: US4753066A] The method of, and apparatus for, producing a yarn using a friction spinning device comprising a perforated first friction spinning drum and a second friction spinning drum which can also be perforated. Two fiber feed passages project to the first friction spinning drum and are each supplied by opening assemblies which individualize or individually separate the fibers. The fibers are transported toward the first friction spinning drum using a feed air stream in the fiber feed passages. This feed air stream is produced by the first friction spinning drum which is maintained under sub-pressure. Advantageously, the fiber double-feed to the friction spinning drum permits supplying two different fiber types to the same yarn end. Also, different inclinations of the fibers at the friction spinning drum can be obtained by different inclinations of the fiber feed passages in order to produce yarns of different character.

IPC 1-7  
**D01H 1/135**

IPC 8 full level  
**D01H 4/06** (2006.01); **D01H 4/16** (2006.01); **D01H 4/38** (2006.01); **D02G 3/04** (2006.01); **D02G 3/26** (2006.01); **D02G 3/36** (2006.01)

CPC (source: EP US)  
**D01H 4/06** (2013.01 - EP US); **D02G 3/36** (2013.01 - EP US)

Cited by  
AT391894B; DE10215453A1

Designated contracting state (EPC)  
AT BE CH DE FR GB IT LI NL

DOCDB simple family (publication)  
**EP 0178466 A1 19860423**; **EP 0178466 B1 19891220**; AT E48852 T1 19900115; AU 4835085 A 19860424; AU 577410 B2 19880922; CN 1008277 B 19900606; CN 85106677 A 19860410; DE 3574883 D1 19900125; IN 165873 B 19900203; JP H0149805 B2 19891026; JP S6197429 A 19860515; JP S6477638 A 19890323; US 4753066 A 19880628; US 4773209 A 19880927; US 4854118 A 19890808

DOCDB simple family (application)  
**EP 85111626 A 19850913**; AT 85111626 T 19850913; AU 4835085 A 19851007; CN 85106677 A 19850905; DE 3574883 T 19850913; IN 627MA1985 A 19850813; JP 21868488 A 19880902; JP 22707985 A 19851014; US 16702688 A 19880311; US 16702988 A 19880311; US 78990285 A 19851010