

Title (en)

Annunciator identification arrangement in an alarm system.

Title (de)

Einrichtung zur Melderidentifizierung in einer Gefahrenmeldeanlage.

Title (fr)

Dispositif d'identification d'avertisseurs dans un système d'alarme.

Publication

EP 0179248 A1 19860430 (DE)

Application

EP 85111427 A 19850910

Priority

DE 3433476 A 19840912

Abstract (en)

1. Annunciator identification arrangement in an alarm system, especially a fire alarm system, having several two-wire annunciation circuits (ML), which are monitored on closed circuit and are connected to an evaluation device (AWE) at a control centre (Z) and to which several annunciators (M1, M2,...) are connected in each case, an alarm-triggering annunciator causing a voltage dip in the line voltage (UL) concerned by virtue of limiting the line current (IL) from the control centre to a first current limiting voltage, and an alarm annunciation of the annunciation circuit (ML) concerned being derived therefrom in the control centre (Z), and the control centre (Z) sending current pulses (IPZ) with a second, increased current limiting value to the annunciation circuit (ML) concerned, the alarm-triggering annunciator causing an increased current flow on the annunciation circuit, characterized in that an annunciator supplementary circuit arrangement (Mzs) is assigned to each annunciator (M1, M2,...) and together with the annunciator composes an annunciator unit (ME1, ME2,...), in that the annunciator supplementary circuit arrangement (Lzs) has an annunciator display (MA) connected to the annunciator circuit (ML) via a controllable switching element (TR1), a pulse divider (IPT) to which the current pulses (IPZ) are applied, and the divider ratio of which can be adjusted by means of switches (S1-Sn) in order to form an annunciator address, and a current reducing device (SRE) arranged in the annunciator connecting branch (1-a) and capable of being triggered by the pulse divider (IPT), the annunciator display (MA) of the alarm-triggering annunciator being switched in with each current pulse (IPZ), and the pulse divider (IPT) being switched further into its original state with the first current pulse (IPZ) and as far as its preset value with each further current pulse (IPZ), and the pulse divider (IPT) further delivering a control signal to the current reducing device (SRE) upon reaching its preset value, and in that there is arranged in the control centre (Z) of the evaluation device (AWE) an annunciator identification circuit arrangement (Mis), which has a current measuring device (Sme) for monitoring the line current (IL), an analog-digital converter (Ad), to the first input (E) of which the measured line current is applied, and a microcomputer (Mr) downstream of the analog-digital converter (Ad) with a display device (Anz) for the annunciator address, the digitised current values being fed from the output (Qw) of the analog-digital converter (Ad) to the microcomputer (Mr), which is connected with a further input (F) of the analog-digital converter (Ad) on the one hand, and to which are applied the current pulses (IPZ) of the increased line current (flashing rate), on the other hand, it being the case, further, that the current pulses (IPZ) are counted up to the current-reduced pulse and the address of the alarm-triggering annunciator is derived therefrom and displayed.

Abstract (de)

Die Einrichtung zur Melderidentifizierung weist in der Zentrale (Z) der Auswerteeinrichtung (AWE) zugeordnet eine Melderidentifizierungs-Schaltungsanordnung (Mis) und jedem Melder (M1, M2, ...) zugeordnet eine Melderzusatz-Schaltungsanordnung (Mzs) auf, die ein steuerbares Schaltelement (Tr1), das aufgrund des alarmauslösenden Melders eingeschaltet wird, eine einstellbaren Impulsteiler (Ipt) und eine Stromreduzierungsseinrichtung (Sre) im Anschlußzweig des Melders (M1) aufweist. Im Alarmfall werden auf die betreffende Meldeleitung (ML) Stromimpulse (Ipz) mit einem erhöhten Stromangebot gegeben, die in der Melderzusatz-Schaltungsanordnung (Mzs) des alarmauslösenden Melders über das steuerbare Schaltelement (Tr1) den Impulsteiler (Ipt) bis zu seinem eingestellten Wert (Melderadresse) weiterschalten, so daß dadurch der letzte Stromimpuls mittels der Stromreduzierungsseinrichtung signifikant geschwächt wird. Mit der Melderidentifizierungs-Schaltungsanordnung (Mis) wird der reduzierte Stromimpuls erkannt. Dabei werden die Stromimpulse mitgezählt, so daß hieraus die Adresse des alarmauslösenden Melders ermittelt und angezeigt (Anz) werden kann.

IPC 1-7

G08B 25/00; G08B 26/00

IPC 8 full level

G08B 25/00 (2006.01); G08B 25/04 (2006.01); G08B 26/00 (2006.01)

CPC (source: EP)

G08B 25/04 (2013.01); G08B 26/002 (2013.01)

Citation (search report)

- [A] DE 2245928 A1 19740404 - PREUSSAG AG FEUERSCHUTZ
- [A] DE 2935335 A1 19810319 - SIEMENS AG
- [A] CH 473432 A 19690531 - SIEMENS AG [DE]
- [A] DE 2230934 B1 19730215
- [AD] DE 2533382 B1 19761021 - SIEMENS AG
- [A] FR 2319166 A1 19770218 - SIEMENS AG [DE]
- [A] FR 2319165 A1 19770218 - SIEMENS AG [DE]

Cited by

DE102015223207A1

Designated contracting state (EPC)

AT BE DE FR GB IT NL SE

DOCDB simple family (publication)

EP 0179248 A1 19860430; EP 0179248 B1 19890531; AT E43733 T1 19890615; DE 3570780 D1 19890706

DOCDB simple family (application)

EP 85111427 A 19850910; AT 85111427 T 19850910; DE 3570780 T 19850910