

Title (en)
FILLING ARRANGEMENT FOR FILLING CLOSED LIQUID HEATING CIRCUITS

Publication
EP 0179271 B1 19900411 (DE)

Application
EP 85111774 A 19850918

Priority
DE 3435127 A 19840925

Abstract (en)
[origin: EP0179271A2] 1. Filling device for introducing fresh water into a closed heating installation, comprising (a) a pressure reductor (1) connected on the inlet side to a fresh water conduction, (b) a tube separator (20) connected to the outlet side of the pressure reductor (1) and having a water-carrying movable member (23), - which in a first operative position is advanced and establishes a connection between a fresh water outlet (22) communicating with the outlet of the pressure reductor (1) and the heating installation, bridging a point of separation (15), - which, in a resting position, ends upstream from the point of separation and closes the fresh water outlet (22), and - which is displaceable by a servomotor to which is applied the fresh water pressure from the resting position to the operative position, (c) a backflow preventor (7) arranged downstream from the tube separator (20) and the point of separation (15) and connected to an inlet of the heating system, and (d) a control arrangement (40) arranged to control the application of the fresh water pressure to the servomotor, characterized in that (e) the control arrangement (40) comprises a differential pressure sensor (41) on which is applied, on one side, the pressure from the outlet of the pressure reductor (1) and, on the other side, the pressure in the heating system, (f) the servomotor for the tube separator (20) is arranged to be controlled by the differential pressure sensor (41) such that - the tube separator (20) is moved, with a first pressure in the heating installation which is equal to the pressure at the outlet of the pressure reductor, to its resting position, and - the tube separator (20) is arranged to be advanced to its operative position with a second pressure in the heating installation which is less than the first pressure.

IPC 1-7
F24D 3/10; F24D 19/10

IPC 8 full level
F24D 3/10 (2006.01); **F24D 19/10** (2006.01)

CPC (source: EP US)
F24D 3/10 (2013.01 - EP); **F24D 3/1083** (2013.01 - EP); **F24D 19/1036** (2013.01 - EP US)

Cited by
GB2528912A; EP0972995A1; EP1239231A3; GB2437175A; EP1452652A3

Designated contracting state (EPC)
AT CH DE FR LI

DOCDB simple family (publication)
EP 0179271 A2 19860430; EP 0179271 A3 19880107; EP 0179271 B1 19900411; AT E51955 T1 19900415; DE 3435127 A1 19860403; DE 3577136 D1 19900517

DOCDB simple family (application)
EP 85111774 A 19850918; AT 85111774 T 19850918; DE 3435127 A 19840925; DE 3577136 T 19850918