

Title (en)
LIGHTING FIXTURE FOR HUMID ENVIRONMENTS

Publication
EP 0179453 B1 19890517 (DE)

Application
EP 85113435 A 19851023

Priority
DE 8431426 U 19841026

Abstract (en)
[origin: EP0179453A1] 1. Moisture-proof luminaire (1) having a housing (2) which is covered by a transparent bowl (5) and a circumferential seal (12) in a splashproof manner and in which various installation devices, such as a ballast (14), connecting terminals (15), luminaire wiring, etc., and at least one lamp holder (18) for a fluorescent lamp (19) are attached to an attachment rail (3) provided with a reflector (4), characterized in that part of the installation devices is attached to the longer leg (13) of an essentially L-shaped attachment rail (3), which longer leg (13) extends in the direction of the longitudinal lamp axis, that the lamp holder (18) is attached to the shorter leg (16) of said attachment rail (3), which shorter leg (16) extends in a direction perpendicular of the longitudinal lamp axis, and that the lamp holder (18), located below the raised edge (10) of the housing in the area covered by the bowl (5), extends between the short leg (16) and one end of the bowl, while the reflector (4) extends between the ballast (14) and the inserted lamp (19) from the shorter leg (16) to the other end of the bowl in spaced relationship from and parallel to the longer leg (13) of the attachment rail (3).

IPC 1-7
F21S 3/02

IPC 8 full level
F21V 15/01 (2006.01); **F21V 17/16** (2006.01); **F21V 19/00** (2006.01); **F21V 23/00** (2006.01); **F21V 31/00** (2006.01); **F21V 23/02** (2006.01); **F21V 27/02** (2006.01); **F21Y 103/00** (2006.01); **F21Y 103/37** (2016.01)

CPC (source: EP)
F21V 15/01 (2013.01); **F21V 17/164** (2013.01); **F21V 19/0095** (2013.01); **F21V 31/00** (2013.01); **F21V 23/026** (2013.01); **F21V 27/02** (2013.01); **F21Y 2103/37** (2016.07)

Citation (examination)
DE 8329137 U1 19840209

Cited by
MD2344C2; DE19847761C1; EP0327014A3; EP0947766A3; AU2004263632B2; GB2294752A; EA008009B1; EP1795799A1; EP2148132A3; AU780967B2; CZ298874B6; US7585086B2; WO2007065584A1; WO2005015082A1; EP1052454A1; US6390654B1; EP2148132A2; JP2006528829A; WO0173342A1; WO03058118A1; WO03006877A3

Designated contracting state (EPC)
AT CH DE LI

DOCDB simple family (publication)
EP 0179453 A1 19860430; EP 0179453 B1 19890517; AT E43170 T1 19890615; DE 3570275 D1 19890622; DE 8431426 U1 19850228

DOCDB simple family (application)
EP 85113435 A 19851023; AT 85113435 T 19851023; DE 3570275 T 19851023; DE 8431426 U 19841026