

Title (en)

METHOD AND APPARATUS FOR APPLYING ANTI-LACERATIVE PLASTIC LAYER TO GLASS.

Title (de)

VERFAHREN UND VORRICHTUNG ZUM AUFBRINGEN ANTILAZERATIVEN KUNSTSTOFFSCHICHT AUF GLAS.

Title (fr)

PROCEDE ET APPAREIL D'APPLICATION D'UNE COUCHE PLASTIQUE ANTILACERATION SUR DU VERRE.

Publication

EP 0179862 A4 19880318 (EN)

Application

EP 85902281 A 19850415

Priority

- US 60487684 A 19840427
- US 71706085 A 19850328

Abstract (en)

[origin: WO8505073A1] A unique method for producing an anti-lacerative glass assembly wherein a plastic composite anti-laceration sheet (18) is to be bonded to a glass substrate sheet (14). The plastic anti-laceration sheet includes an inner layer of polyvinyl butyral (20) adapted to abut the glass substrate sheet, an intermediate layer (22) of polyester, and an outer layer (24) of abrasion resistant material. A glass cover sheet (30) having substantially the same curvature as the glass substrate sheet is utilized to press the anti-laceration sheet into bonding engagement with the glass substrate sheet. In accordance with the present invention, the bonding operation is accomplished by heating the laminated glass assembly a predetermined temperature in the range of 285?oF to 305?oF. It has been found that such a temperature must be sufficiently high to cause the intermediate layer of polyester to bond to the inner layer of polyvinyl butyral, and to cause the inner layer of polyvinyl butyral to bond to the glass substrate sheet, and must be sufficiently low to prevent crazing of the abrasion resistant coating. The present invention also concerns the use of a unique vacuum ring construction which is mounted about the periphery of the laminated assembly and is utilized to de-air the assembly. The vacuum ring (36) is provided with a check valve (38) to maintain the vacuum within the ring during periods wherein it is disconnected from a vacuum source. Further, the method of the present invention includes the step of removing a selected portion or portions of the anti-laceration sheet after it has been bonded to the glass substrate sheet to provide an exposed glass surface for use in mounting the glass assembly into an associated frame.

IPC 1-7

B32B 17/00; B32B 31/00

IPC 8 full level

B32B 17/10 (2006.01); B32B 27/36 (2006.01)

CPC (source: EP KR US)

B32B 17/00 (2013.01 - KR); **B32B 17/10036** (2013.01 - EP US); **B32B 17/10045** (2013.01 - EP); **B32B 17/10293** (2013.01 - EP); **B32B 17/10761** (2013.01 - EP US); **B32B 17/10834** (2013.01 - EP); **B32B 17/10889** (2013.01 - EP); **B32B 27/08** (2013.01 - US); **B32B 27/36** (2013.01 - EP US); **B32B 2307/554** (2013.01 - US); **B32B 2307/581** (2013.01 - US); **B32B 2367/00** (2013.01 - EP US); **B32B 2605/00** (2013.01 - US)

Citation (search report)

- [A] FR 2247348 A1 19750509 - SAINT GOBAIN [FR]
- [A] GB 1215471 A 19701209 - GLAVERBEL [BE]
- See references of WO 8505073A1

Cited by

US9391124B2

Designated contracting state (EPC)

AT BE CH FR IT LI

DOCDB simple family (publication)

WO 8505073 A1 19851121; AU 4217985 A 19851128; AU 579371 B2 19881124; BR 8506693 A 19860415; CA 1260374 A 19890926; DE 3590207 T1 19860515; EP 0179862 A1 19860507; EP 0179862 A4 19880318; ES 542608 A0 19860401; ES 8606127 A1 19860401; GB 2176438 A 19861231; GB 2176438 B 19880928; GB 8530652 D0 19860122; KR 860700020 A 19860131; KR 930011145 B1 19931124; NL 8520086 A 19860303; SE 460191 B 19890918; SE 8506058 D0 19851220; SE 8506058 L 19851220; SE 8700879 D0 19870303; SE 8700879 L 19870303

DOCDB simple family (application)

US 8500667 W 19850415; AU 4217985 A 19850415; BR 8506693 A 19850415; CA 479716 A 19850422; DE 3590207 T 19850415; EP 85902281 A 19850415; ES 542608 A 19850426; GB 8530652 A 19850415; KR 850700412 A 19851230; NL 8520086 A 19850415; SE 8506058 A 19851220; SE 8700879 A 19870303