

Title (en)
METHOD FOR PREVENTING OFFSET IN ELECTROPHOTOGRAPHY

Publication
EP 0181081 B1 19920722 (EN)

Application
EP 85306904 A 19850927

Priority
JP 20297684 A 19840929

Abstract (en)
[origin: EP0181081A2] A charged image on a photosensitive layer is developed with a toner containing a releasing agent and a hydroxycarboxylic acid complex salt to form a toner image. The toner image is then transferred to a receptor sheet and fixed to it. The use of a toner containing a specific hydroxycarboxylic acid complex salt brings about a marked advantage of widening a non-offset region to a higher temperature without impairing the antiblocking property, flowability and heat resistance of the toner.

IPC 1-7
G03C 9/08

IPC 8 full level
G03G 13/20 (2006.01); **G03G 9/08** (2006.01); **G03G 9/097** (2006.01)

CPC (source: EP US)
G03G 9/09783 (2013.01 - EP US)

Cited by
EP0280272A3; FR2592184A1; EP0967527A1; EP0941983A1; EP1225165A1; GB2234361A; GB2234361B; US6183927B1; US6261731B1; US6515158B2

Designated contracting state (EPC)
DE FR GB NL

DOCDB simple family (publication)
EP 0181081 A2 19860514; EP 0181081 A3 19870603; EP 0181081 B1 19920722; DE 3586390 D1 19920827; DE 3586390 T2 19930107; JP S6183545 A 19860428; US 4645729 A 19870224

DOCDB simple family (application)
EP 85306904 A 19850927; DE 3586390 T 19850927; JP 20297684 A 19840929; US 78019185 A 19850926