

Title (en)

Cubical construction.

Title (de)

Raumkonstruktion.

Title (fr)

Construction parallélépipédique.

Publication

EP 0182288 A2 19860528 (DE)

Application

EP 85114475 A 19851114

Priority

DE 3442231 A 19841119

Abstract (en)

1. A three-dimensional structure consisting of a supporting frame (1) with wall elements (4) inserted into it, and in particular to a space adapted to hold ventilation equipment, in which the supporting frame consists of horizontal and vertical corner and possibly intermediate legs (2, 3) constituted by hollow box-like sections (leg sections (10, 11)) and connected to one another at their abutting ends by connecting elements, the said connecting elements consisting of a cube-shaped middle piece (16, 17) and, connected thereto, outer pieces (18) onto which the leg sections are fitted, in their longitudinal direction, characterised in that in their cross-section the leg sections (10, 11) have at least two of their corners inlets (13, 15) which receive the edges (9) of adjacent wall elements (4) and in that the connecting members (18), in their cross-section parallel therewith, have in each case a substantially angular form, their outside which forms the outer corner being adapted to one form (10) of leg section while the inside forming the inner corner is adapted to the other form (11) of leg section and in that the connecting pieces can be so connected to the cube-shaped middle piece (16, 17) that either their outer corner or their inner corner (21) is on the outside of the frame.

Abstract (de)

Aus einem Stützrahmen und aus in diesen eingesetzten Wandelementen bestehende Raumkonstruktion, insbesondere Aufnahmeraum für lüftungstechnische Aggregate, bei welcher der Stützrahmen aus Eck- und gegebenenfalls Zwischenstücken besteht, die von Schenkelprofilen gebildet und an ihren zusammenstoßenden Enden durch aus Mittelstück und Anschlußstücken bestehende Verbindungselemente miteinander verbunden sind. Die auf die Anschlußstücke (18) aufschiebbaren Schenkelprofile (10, 11) haben im Querschnitt an mindestens zwei ihrer Ecken die Ränder (9) benachbarter Wandelemente (4) aufnehmende Einsprünge (13, 15). Die Anschlußstücke (18) besitzen im dazu parallelen Querschnitt jeweils etwa Winkelform, wobei deren die Außencke bildende Außenseite der einen Bauform (10) des Schenkelprofils und deren die Innenecke bildende Innenseite der anderen Bauform (11) des Schenkelprofils angepaßt ist. Die Anschlußstücke sind entsprechend an das würfelförmige Mittelstück (16, 17) anschließbar.

IPC 1-7

E04H 1/12; E04B 1/24

IPC 8 full level

E04B 1/24 (2006.01); **E04B 1/58** (2006.01); **E04H 1/12** (2006.01)

CPC (source: EP)

E04B 1/24 (2013.01); **E04B 1/5818** (2013.01); **E04H 1/1238** (2013.01); **E04B 2001/2406** (2013.01); **E04B 2001/2415** (2013.01);
E04B 2001/2448 (2013.01); **E04B 2001/2481** (2013.01)

Cited by

CN102108736A; AT410972B; GB2376030A; GB2376030B; FR2689551A1; EP2759648A1; US8176703B2; WO2007144913A1

Designated contracting state (EPC)

AT BE CH DE FR GB IT LI LU NL SE

DOCDB simple family (publication)

EP 0182288 A2 19860528; EP 0182288 A3 19871111; EP 0182288 B1 19890906; AT E46208 T1 19890915; DE 3442231 A1 19860528;
DE 3572852 D1 19891012

DOCDB simple family (application)

EP 85114475 A 19851114; AT 85114475 T 19851114; DE 3442231 A 19841119; DE 3572852 T 19851114