

Title (en)
Ski binding.

Title (de)
Skibindung.

Title (fr)
Fixation pour ski.

Publication
EP 0183000 A2 19860604 (DE)

Application
EP 85112147 A 19850925

Priority

- AT 94985 A 19850329
- AT 131985 A 19850503
- AT 135585 A 19850507
- AT 135685 A 19850507
- AT 304984 A 19840926

Abstract (en)

1. A ski binding for a cross-country or touring ski, comprising a holding bracket (5, 105, 105', 105", 205, 305) mounted for pivoting about a horizontal transverse axis (3, 103, 103', 103", 203, 303) in unison with a rocking member (4, 104, 104', 104", 204, 304) carrying at least one locking pin (7, 107, 107', 107", 207, 307), in the closed position, and, for the transition between the closed and the released position, relative to said rocking member, said holding bracket (5, 105, 105', 105", 205, 305) in said closed position of the binding gripping a forward sole extension (24) of an inserted boot (22) from above, while at least one locking pin (7, 107, 107', 107", 207, 307) penetrates at least one opening (23) of the sole extension (24) of the boot (22) from below, and a releasable locking mechanism (9, 109, 109', 109", 209, 309) for fixing said holding bracket (5, 105, 105', 105", 205, 305) and said rocking member (4, 104, 104', 104", 204, 304) in position relative to one another in the closed position, said rocking member (4, 104, 104', 104", 204, 304) being pivotable upwards about a transverse axis (3, 103, 103', 103", 203, 303) disposed at a fixed position on the ski at a forward position of said rocker member facing towards the tip of the ski, the transverse axis (3, 103, 103', 103", 203, 303) for pivoting said holding bracket (5, 105, 105', 105", 205, 305) relative to said rocking member (4, 104, 104', 104", 204, 304) being disposed in a front portion of the holding bracket (5, 105, 105', 105", 205, 305) facing towards the tip of the ski, characterized in that there is provided a single transverse axis (3, 103, 103', 103", 203, 303) for pivoting said holding bracket (5, 105, 105', 105", 205, 305) and said rocking member (4, 104, 104', 104", 204, 304) in unison as well as for pivoting said holding bracket (5, 105, 105', 105", 205, 305) relative to said rocking member (4, 104, 104', 104", 204, 304), in that in the closed state of the binding (1, 100, 100', 100", 200, 300) determined by said locking mechanism (9, 109, 109', 109", 209, 309) said holding bracket (5, 105, 105', 105", 205, 305) and said rocking member (4, 104, 104', 104", 204, 304) are non-pivotably interconnected and adapted to be pivoted upwards in unison against the force of a first spring (11, 111, 111', 111", 211a, 311) supported on the base plate (2, 102, 102', 102", 202, 302), in that a second spring (6, 106, 106', 106", 206, 306) acts to bias said holding bracket (5, 105, 105', 105", 205, 305) and said rocking member (4, 104, 104', 104", 204, 304), and in that said holding bracket (5, 105, 105', 105", 205, 305) is formed as a shell having a bottom (5a, 105a, 105'a, 105"a, 205a, 305a, 405a) formed with at least one opening (15, 15', 115, 115', 115", 215, 315), and two lateral guides (5b, 105b, 105'b, 105"b, 205b, 305b), said locking pin, or pins (7, 107, 107', 107", 207, 307) extending into said opening(s) in the closed state of the binding (1, 100, 100', 100", 200, 300), whereas in the released state of the binding (1, 100, 100', 100", 200, 300) said locking pin or pins, respectively, (7, 107, 107', 107", 207, 307) is (or are) retracted from said opening(s) (15, 15', 115, 215, 315) of said bottom (5a, 105a, 105'a, 105"a, 205a, 305a) of said holding bracket (5, 105, 105', 105", 205, 305) and from said sole extension (24) of said boot (22) due to said rocking member (4, 104, 104', 104", 204, 304) and said holding bracket (5, 105, 105', 105", 205, 305) being spread apart by the action of said second spring (6, 106, 106', 106", 206, 306).

Abstract (de)

Diese Skibindung ist für einen Langlauf- oder Tourenski bestimmt und besitzt einen Haltebügel od. dgl., welcher in der Schließstellung der Bindung eine vordere Sohlenverlängerung des Schuhs übergreift, wobei Verriegelungszapfen Öffnungen in der Sohlenverlängerung durchsetzen, wogegen in der Offenstellung die Verriegelungszapfen aus dem Inneren des Haltebügels entfernt sind. Um bei einer derartigen Skibindung die Länge des zur Befestigung des Skischuhs erforderlichen Sohlenfortsatzes herabzusetzen und gleichzeitig die Verankerung des Skischuhs in der Bindung zu verbessern, sieht die Erfindung vor, daß der Haltebügel (1) sowohl gemeinsam mit einem die Verriegelungszapfen (2) tragenden Schwenkteil (3) wie relativ zu diesem um eine horizontale Querachse (4) schwenkbar gelagert ist, wobei die Relativbewegung von Haltebügel (1) und Verriegelungszapfen (2) dem Übergang zwischen Schließ- und Offenstellung entspricht, daß eine lösbare Sperre die Schließstellung fixiert und eine Feder (5) Haltebügel (1) und Schwenkteil (3) im Sinne einer Trennung belastet.

IPC 1-7
A63C 9/20

IPC 8 full level
A63C 9/20 (2012.01)

CPC (source: EP)
A63C 9/20 (2013.01)

Cited by
US4925206A; US6402184B1; EP0257282A3; FR2616079A2; EP0254094A3; FR2622462A1; US5193840A; AT398279B; FR2610836A1; AT390384B; US4909532A; DE3612658A1; WO8707845A1; WO9115275A1

Designated contracting state (EPC)
CH DE FR LI

DOCDB simple family (publication)
EP 0183000 A2 19860604; EP 0183000 A3 19870401; EP 0183000 B1 19900425; DE 3577278 D1 19900531

DOCDB simple family (application)
EP 85112147 A 19850925; DE 3577278 T 19850925