

Title (en)  
TUBE WRENCH

Publication  
**EP 0184073 B1 19890802 (DE)**

Application  
**EP 85114748 A 19851120**

Priority  
DE 3444725 A 19841207

Abstract (en)  
[origin: US4616536A] The wrench comprise two levers (10,21). A jaw (15) is fixed to the one lever (10) on which a slider (17) is displaceable to adjust the mouth width. The second lever (21) is disposed at the slider (17) by means of a hinge (23). The second jaw (25) is tiltably mounted at the lever (21) by means of a hinge (24), the tilting movements being limited by two stops (26 and 27). At least one stop (27) is provided at a sliding element (29) which, responsive to the position of the second lever (21) is adapted to recede to permit, with an empty return movement of the pipe tongs a stronger tilting movement of the second jaw (25).

IPC 1-7  
**B25B 13/16; B25B 13/18; B25B 13/50**

IPC 8 full level  
**B25B 13/16** (2006.01); **B25B 13/18** (2006.01); **B25B 13/32** (2006.01); **B25B 13/50** (2006.01)

CPC (source: EP US)  
**B25B 13/16** (2013.01 - EP US); **B25B 13/32** (2013.01 - EP US); **B25B 13/505** (2013.01 - EP US)

Cited by  
EP3175953A4

Designated contracting state (EPC)  
DE FR GB IT SE

DOCDB simple family (publication)  
**EP 0184073 A2 19860611; EP 0184073 A3 19870616; EP 0184073 B1 19890802**; DE 3444725 A1 19860612; DE 3571951 D1 19890907; ES 296294 U 19870801; ES 296294 Y 19880216; US 4616536 A 19861014

DOCDB simple family (application)  
**EP 85114748 A 19851120**; DE 3444725 A 19841207; DE 3571951 T 19851120; ES 296294 U 19851205; US 80697885 A 19851209