

Title (en)
Siphon

Publication
EP 0185109 A1 19860625 (DE)

Application
EP 84115706 A 19841218

Priority
EP 84115706 A 19841218

Abstract (en)

1. Odour trap wherein, in a rectilinearly downwardly extending flow path (A-B) there is, pivotable about an axis (4) disposed outside the flow path (A-B) a flap (1) which, in the position of rest and under the action of a counterweight (5) which counteracts the force of gravity of the flap, bears on the underside of a seating (2) which is inclined obliquely downwardly in relation to the pivot axis (4) of the flap and which pivots downwardly when subjected to the loading of liquid striking it (1) from above, characterised in that the flap (1) and the seat (2) are disposed in a tubular main housing part (6) which is to be incorporated into the fluid pipe, in particular between a water outlet pipe and a sewer connecting pipe, the counterweight (5) being disposed in a housing projection (7) which is laterally adjacent the main housing part (6), and in that one half of the cross-section of the tubular main part (6) engages into the box-like housing projection (7) and in that the casing (13) of the tubular main part (6) in the housing projection (7) has a cut-out (15, 16) which extends over the half cross-section from the seat (2) as far as the bottom end (14) of the housing projection (7) and in that the housing projection (7) is tightly sealed by a removable cover (20) and in that the flap (1) together with the counterweight (5) can, once the cover (20) has been removed, be withdrawn from the housing (6, 7) so that a wire cleaning brush can be introduced through the housing projection (7) and into the cavity in the main housing part (6) which extends under the seat (2) and into the liquid pipe which is adjacent thereto.

Abstract (de)

Der Geruchsverschluss hat einen gerade abwärts verlaufenden Stromungsweg (A-B), in dem eine Klappe (1) angeordnet ist. Die Klappe (1) ist um eine ausserhalb des Strömungsweges (A-B) angeordnete Achse (4) schwenkbar und in ihrer Ruhelage an der Unterseite eines, bezogen auf ihre Schwenkkachse (4) nach unten geneigt angeordneten Sitzes (2) gehalten, so dass sie bei Belastung durch von oben auftreffende Flüssigkeit nach unten schwenkt. Dieser Geruchsverschluss neigt nicht zu Verstopfungen und ist leicht zu reinigen. Da er kein stehendes Wasser enthält, bleibt er auch wirksam, wenn ein üblicher Wasserverschluss wegen Verdunstung des Wassers undicht würde, und er kann auch nicht einfrieren.

IPC 8 full level

E03C 1/122 (2006.01); **E03C 1/298** (2006.01)

CPC (source: EP)

E03C 1/122 (2013.01); **E03C 1/298** (2013.01)

Citation (search report)

- [Y] CH 212375 A 19401130 - T MASCHINENBAU AKTIENGESELLSCH [CH]
- [Y] DE 1084655 B 19600630 - CARL BIRKNER
- [Y] US 1328103 A 19200113 - RIPPLE JOHN W
- [A] US 1436331 A 19221121 - AYLING ARTHUR W
- [A] EP 0111716 A2 19840627 - KESSEL BERNHARD
- [A] FR 666735 A 19291004

Cited by

DE202004020197U1; CN113622487A; EP0278746A3; US4867802A; CN104695514A; EP3128088A1; FR3039842A1; RU2731475C2;
WO2005014942A1

Designated contracting state (EPC)

AT BE CH DE FR GB IT LI LU NL SE

DOCDB simple family (publication)

EP 0185109 A1 19860625; EP 0185109 B1 19880928; AT E37577 T1 19881015; DE 3474328 D1 19881103

DOCDB simple family (application)

EP 84115706 A 19841218; AT 84115706 T 19841218; DE 3474328 T 19841218