

Title (en)

METHOD OF MAKING MALE ELEMENTS FOR HINGE DEVICES AND HINGE DEVICES OBTAINED THEREBY

Publication

EP 0187656 B1 19900411 (EN)

Application

EP 86100126 A 19860107

Priority

IT 8250385 A 19850109

Abstract (en)

[origin: EP0187656A2] The present invention has for its subject a hinge and a method of forming a closed cavity hollow male hinge. The method comprises a first processing step consisting of shearing a section from a cylindrival drawn blank followed by cold impact reverse-extrusion by means of a punch and die action; that step causes the material to be upturned laterally to form a constant pattern hollow body having an open end. Thereafter, there is carried out on said hollow body, as by striking with a die, a reduction of one portion thereof at the open end, thus defining a hollow pin. The open end of the latter is then upset and stopped to make the hollow body watertight.

IPC 1-7

B21K 13/02; E05D 5/10

IPC 8 full level

B21K 13/02 (2006.01); E05D 5/10 (2006.01)

CPC (source: EP)

B21K 13/02 (2013.01); E05D 5/10 (2013.01); E05D 2005/102 (2013.01)

Cited by

IT202000016414A1; EP2199512A1; ITUD20080273A1

Designated contracting state (EPC)

CH DE FR IT LI

DOCDB simple family (publication)

EP 0187656 A2 19860716; EP 0187656 A3 19861001; EP 0187656 B1 19900411; DE 3670224 D1 19900517; ES 296110 U 19871016;
ES 296110 Y 19880416; ES 551291 A0 19870501; ES 8704772 A1 19870501; IT 1187411 B 19871223; IT 8582503 A0 19850109

DOCDB simple family (application)

EP 86100126 A 19860107; DE 3670224 T 19860107; ES 296110 U 19870115; ES 551291 A 19860109; IT 8250385 A 19850109