

Title (en)

Stapling machine for fastening a closure element, such as a snap fastener, to a supporting web such as a garment.

Title (de)

Nietpresse zur Befestigung eines Schliessfunktions-Teils, insbesondere Druckknopfteils, an einer Trägerbahn, wie einem Kleidungsstück.

Title (fr)

Presse à riveter pour fixer un élément de fermeture tel qu'un bouton-pression à un support tel qu'un vêtement.

Publication

**EP 0187995 A2 19860723 (DE)**

Application

**EP 85116427 A 19851221**

Priority

DE 3501224 A 19850116

Abstract (en)

[origin: US4703882A] A riveting press wherein the female component of a composite button, knob or a like article of hardware is introduced between the jaws of first tongs below a sheet of textile material whose marked side faces upwardly, and wherein the male component of the article is introduced between the jaws of second tongs at a level above the sheet. The first tongs deposit the female component on a stationary anvil while the second tongs descend toward the upper side of the sheet to place the male component into the path of movement of a descending ram which causes a deformable part of the male component to penetrate through the sheet and to be deformed into permanent engagement with the female component by a centering stud which is provided on the anvil. The mechanism which moves the first tongs up and down derives motion from the mechanism which moves the second tongs and the ram.

Abstract (de)

Bei einer Nietpresse zur Befestigung eines Schließfunktionen ausübenden Teils (Funktionsteils) an einer Trägerbahn wird ein verformbare Halteelemente aufweisender Befestigungs-teil verwendet. Zur Positionierung dieser Teile besitzt die Presse Unterwerkzeuge und Oberwerkzeuge, zu denen jeweils ein Unterstempel und ein Oberstempel gehören. Für eine bequeme Handhabung und zuverlässige Nietung empfiehlt es sich, die Oberwerkzeuge das Befestigungsteil und die Unterwerkzeuge das Funktionsteil positionieren zu lassen und die Unterwerkzeuge mit einer Bühne und einem darauf befindlichen spreizbeweglichen Paar von Backen (Unterbacken) zu versehen, die zwischen sich ein Aufnahmeprofil für das Funktionsteil aufweisen. Die Unterbacken sind dabei mit einem eigenen Hubtrieb versehen, der die Unterbacken unter die Stirnfläche des Unterstempels absenkt, wobei Steuerflächen zwischen den Unterbacken eine selbsttätige Spreizbewegung der Unterbacken bei ihrer Hubbewegung ausführen lassen. Auf der Stirnfläche des Unterstempels sind Richtelemente zur Lagesicherung des Funktionsteils vorgesehen.

IPC 1-7

**A41H 37/04**

IPC 8 full level

**A41H 37/10** (2006.01); **A41H 37/04** (2006.01)

CPC (source: EP US)

**A41H 37/04** (2013.01 - EP US)

Designated contracting state (EPC)

AT BE DE FR GB IT NL SE

DOCDB simple family (publication)

**EP 0187995 A2 19860723**; **EP 0187995 A3 19870902**; **EP 0187995 B1 19891018**; DE 3501224 A1 19860717; DE 3573709 D1 19891123; FI 84688 B 19910930; FI 84688 C 19920110; FI 860108 A0 19860110; FI 860108 A 19860717; JP H0765242 B2 19950712; JP S61167005 A 19860728; US 4703882 A 19871103

DOCDB simple family (application)

**EP 85116427 A 19851221**; DE 3501224 A 19850116; DE 3573709 T 19851221; FI 860108 A 19860110; JP 149086 A 19860109; US 81879186 A 19860114