

Title (en)
PAD-DYEING PROCESS FOR WOOL

Publication
EP 0189851 B1 19890621 (DE)

Application
EP 86100899 A 19860123

Priority
DE 3502960 A 19850130

Abstract (en)
[origin: US4640691A] Vinylsulfonyl dyes, if padded from acidic liquors, produce on wool merely dyeings having a poor yield and only moderate fastness properties if the pad-beam method is used. It has been found according to the invention that padding from weakly alkaline liquor (pH 7-9) with sodium bicarbonate as fixing alkali and subsequent batching (6-24 hours) of the material produces good coloristic results especially on wools with a low-felting or non-felting finish.

IPC 1-7
D06P 3/14

IPC 8 full level
D06P 3/14 (2006.01)

CPC (source: EP US)
D06P 3/148 (2013.01 - EP US); **Y10S 8/917** (2013.01 - US)

Designated contracting state (EPC)
AT CH DE FR IT LI

DOCDB simple family (publication)
EP 0189851 A2 19860806; EP 0189851 A3 19870204; EP 0189851 B1 19890621; AT E44167 T1 19890715; DE 3502960 A1 19860731; DE 3664063 D1 19890727; JP H0718094 B2 19950301; JP S61179385 A 19860812; US 4640691 A 19870203

DOCDB simple family (application)
EP 86100899 A 19860123; AT 86100899 T 19860123; DE 3502960 A 19850130; DE 3664063 T 19860123; JP 1487886 A 19860128; US 82346886 A 19860128