

Title (en)
SECURING CLAMP AND FASTENING DEVICE FOR RAILWAY RAILS

Publication
EP 0194550 B1 19890906 (DE)

Application
EP 86102794 A 19860304

Priority
• DE 3509472 A 19850315
• DE 3509473 A 19850315

Abstract (en)
[origin: US4718604A] The invention describes a clamp for rails that is produced from resilient steel bar with multiple bends. The first section (11) of the rail clamp (9, 10) is essentially horizontally arranged, while the last section (14) rests on the rail flange (5). The second section (12) curves upwards in the vertical plane that passes through the first section (11). The remaining sections of the clamp lie all on the side of the first section that faces the rail. The fastening arrangement comprises an anchoring part (20) where the supporting surface (23) for a supporting section of the clamp (9, 10) is located essentially vertically above the locating hole (24) of the clamp (9, 10). That produces a relatively short clamp requiring a minimum of material.

IPC 1-7
E01B 9/30

IPC 8 full level
E01B 9/30 (2006.01)

CPC (source: EP KR US)
E01B 9/303 (2013.01 - EP US); **E01B 9/60** (2013.01 - KR)

Citation (examination)
• GB 1305871 A 19730207
• GB 1132205 A 19681030 - MILLS JAMES LTD

Cited by
FR2701276A1; BE1007312A3; US5474233A

Designated contracting state (EPC)
AT BE DE GB IT LU NL SE

DOCDB simple family (publication)
EP 0194550 A2 19860917; EP 0194550 A3 19861120; EP 0194550 B1 19890906; AT E46201 T1 19890915; AU 5441986 A 19860918; AU 574904 B2 19880714; BR 8601157 A 19861125; CA 1332829 C 19941101; CA 1337563 C 19951114; CN 1004642 B 19890628; CN 86102427 A 19860917; DE 3665492 D1 19891012; JP H0723601 B2 19950315; JP S61211401 A 19860919; KR 860007425 A 19861013; KR 950010519 B1 19950919; US 4718604 A 19880112

DOCDB simple family (application)
EP 86102794 A 19860304; AT 86102794 T 19860304; AU 5441986 A 19860307; BR 8601157 A 19860314; CA 503202 A 19860304; CA 616895 A 19940803; CN 86102427 A 19860314; DE 3665492 T 19860304; JP 5673486 A 19860314; KR 860001896 A 19860315; US 83759486 A 19860307