

Title (en)
ELECTROMAGNETICALLY OPERATING ADJUSTMENT SYSTEM

Publication
EP 0197357 A3 19870527 (DE)

Application
EP 86103469 A 19860314

Priority
DE 3513107 A 19850412

Abstract (en)
[origin: US4682574A] An electromagnetic positioning system in displacement machines such as internal combustion engines in which spring-loaded valve actuators are shifted between two operating positions. Upon startup, the locus of equilibrium of the spring system is shifted by means of an adjusting solenoid which moves one of the spring system supporting seat members. The support seat member for the spring system is secured to and guided by a sleeve which, upon startup, is guided along the actuator rod. When the device is in its operating position, the actuator rod is guided in the sleeve. The working surface of the adjusting solenoid core has a beveled surface which assists in centering the sleeve in its operating position. The invention is particularly applicable to lifting valves and sliding gate valves, e.g., intake and exhaust valve actuators.

IPC 1-7
F01L 9/04

IPC 8 full level
F01L 9/04 (2006.01); **F01L 9/20** (2021.01); **H01F 7/16** (2006.01); **H01F 7/18** (2006.01)

CPC (source: EP US)
F01L 9/20 (2021.01 - EP US)

Citation (search report)
• [AD] DE 3024109 A1 19820121 - PISCHINGER FRANZ PROF DIPL ING [DE]
• [A] EP 0118591 A1 19840919 - KLOECKNER WOLFGANG DR
• [A] FR 2542373 A1 19840914 - FEV FORSCH ENERGIETECH VERBR [DE]

Cited by
US5813653A; US5199392A; EP0405189A1; EP1069285A2; EP0796981A1; WO9001614A1; EP0356713B1

Designated contracting state (EPC)
BE DE FR GB IT NL SE

DOCDB simple family (publication)
EP 0197357 A2 19861015; EP 0197357 A3 19870527; EP 0197357 B1 19890111; CA 1272085 A 19900731; DE 3513107 A1 19861016; DE 3513107 C2 19890608; DE 3661756 D1 19890216; ES 296853 U 19880201; ES 296853 Y 19880916; JP H069170 B2 19940202; JP S61240611 A 19861025; US 4682574 A 19870728

DOCDB simple family (application)
EP 86103469 A 19860314; CA 506460 A 19860411; DE 3513107 A 19850412; DE 3661756 T 19860314; ES 296853 U 19860409; JP 8395986 A 19860410; US 85093786 A 19860411