

Title (en)

SAW DEVICES WITH REFLECTION-SUPPRESSING FINGERS

Publication

EP 0197640 A3 19871216 (EN)

Application

EP 86301277 A 19860221

Priority

CA 477948 A 19850329

Abstract (en)

[origin: EP0197640A2] 57 Each IDT (inter-digital transducer) (12, 14) of a SAW (surface acoustic wave) device has a linearly tapered back edge formed by reflection-suppressing fingers (18, 26) of successively decreasing length spaced apart with a pitch of lambda/4 behind the active region (16, 24) of the IDT, where lambda is the wavelength of a SAW to be propagated, whereby [SAW reflections at the back edge of the IDT are substantially eliminated. A thin resistive doped sili- r con film (40, 42) between the back edge of each IDT and the adjacent edge (36, 38) of the substrate absorbs waves propagated via this back edge. The film underlies the IDTs to provide improved adhesion to the substrate.

IPC 1-7

H03H 9/02

IPC 8 full level

H03H 9/145 (2006.01); **H03H 3/08** (2006.01); **H03H 9/02** (2006.01); **H03H 9/25** (2006.01)

CPC (source: EP US)

H03H 9/02842 (2013.01 - EP US)

Citation (search report)

[A] US 4350963 A 19820921 - IWAMOTO HISAO, et al

Cited by

DE3731309A1

Designated contracting state (EPC)

AT CH DE FR GB LI NL SE

DOCDB simple family (publication)

EP 0197640 A2 19861015; EP 0197640 A3 19871216; EP 0197640 B1 19911127; EP 0197640 B2 19961211; AT E69917 T1 19911215;
AU 5444186 A 19861002; AU 576417 B2 19880825; CA 1254994 A 19890530; DE 3682605 D1 19920109; JP S61227418 A 19861009;
US 4642507 A 19870210

DOCDB simple family (application)

EP 86301277 A 19860221; AT 86301277 T 19860221; AU 5444186 A 19860307; CA 477948 A 19850329; DE 3682605 T 19860221;
JP 6884886 A 19860328; US 71858985 A 19850401