

Title (en)

AMORPHOUS SILICON PHOTORECEPTORS FOR ELECTROPHOTOGRAPHY, PROCESS FOR THE PREPARATION AND/OR REGENERATION THEREOF, AND METHOD FOR THE ELECTROPHOTOGRAPHY USING SUCH MATERIALS

Publication

EP 0198363 A3 19880601 (EN)

Application

EP 86104635 A 19860404

Priority

- JP 7235585 A 19850405
- JP 7235685 A 19850405
- JP 26187985 A 19851121
- JP 26329285 A 19851122
- JP 26329385 A 19851122
- JP 26329485 A 19851122
- JP 26454685 A 19851125
- JP 26454785 A 19851125

Abstract (en)

[origin: EP0198363A2] An amorphous silicon photoreceptor for electrophotography having a specific surface roughness is disclosed herein. Also provided are a process for the preparation and/or regeneration of the material and improved methods for electrophotography, which use a special abrasive. The material enables the electrophotography without occurrence of any image blurring under high humidity conditions.

IPC 1-7

G03G 5/082

IPC 8 full level

G03G 5/08 (2006.01); **G03G 5/082** (2006.01); **G03G 21/00** (2006.01)

CPC (source: EP US)

G03G 5/08214 (2013.01 - EP US); **G03G 21/00** (2013.01 - EP US)

Citation (search report)

- [Y] US 4364329 A 19821221 - MURAI KEIICHI, et al
- [Y] FR 2172129 A1 19730928 - RICOH KK [JP]
- [Y] DE 3428433 A1 19850221 - CANON KK [JP]
- [Y] DE 2708061 A1 19770908 - RICOH KK
- [Y] US 3900588 A 19750819 - FISHER DONALD J
- [XP] PATENT ABSTRACTS OF JAPAN, vol. 9, no. 122 (P-359)[1845], 28th May 1985; & JP-A-60 007 433 (STANLEY DENKI K.K.) 16-01-1985

Cited by

EP0671671A1; GB2200079A; US4931841A; GB2200079B

Designated contracting state (EPC)

AT BE CH DE FR GB IT LI NL SE

DOCDB simple family (publication)

EP 0198363 A2 19861022; EP 0198363 A3 19880601; AU 5562986 A 19861009; AU 587812 B2 19890831; CA 1267804 A 19900417;
US 4764448 A 19880816

DOCDB simple family (application)

EP 86104635 A 19860404; AU 5562986 A 19860403; CA 505920 A 19860404; US 84740986 A 19860402