

Title (en)

LIGHT FIXTURE, PARTICULARLY FOR EMERGENCY LIGHTING

Publication

EP 0199230 B1 19910109 (DE)

Application

EP 86105058 A 19860412

Priority

DE 3513498 A 19850416

Abstract (en)

[origin: EP0199230A2] To form this light fixture, two hollow bodies (11, 12) are provided which extend with their longitudinal axes parallel to one another and at a distance from one another and, on the one hand, are closed at their end faces and, on the other hand, are held at a distance from one another, by means of cover parts applied to the end faces. Between the two hollow bodies (11, 12), a reflector (38) is clamped. One of the two hollow bodies accommodates the batteries or accumulators (37) and the other one of the two hollow bodies (11) accommodates heat-generating components such as ballast (34) and the like. <IMAGE>

IPC 1-7

F21S 9/02; F21V 17/00

IPC 8 full level

F21S 9/02 (2006.01); F21V 15/01 (2006.01); F21V 15/015 (2006.01); F21V 17/00 (2006.01); F21V 17/16 (2006.01); F21V 23/02 (2006.01); F21V 29/15 (2015.01); F21V 7/00 (2006.01); F21V 17/10 (2006.01); F21V 21/02 (2006.01)

CPC (source: EP US)

F21S 9/022 (2013.01 - EP US); F21V 15/01 (2013.01 - EP); F21V 15/015 (2013.01 - EP); F21V 17/164 (2013.01 - EP); F21V 23/02 (2013.01 - EP); F21V 29/15 (2015.01 - EP); F21V 7/005 (2013.01 - EP); F21V 15/013 (2013.01 - EP); F21V 17/104 (2013.01 - EP); F21V 17/16 (2013.01 - EP); F21V 21/02 (2013.01 - EP); F21Y 2103/00 (2013.01 - EP US)

Cited by

FR2674316A1; EP0950849A3; EP0677698A1; EP1004816A1; FR2786255A1; GB2363839A; FR2810724A1; GB2363839B

Designated contracting state (EPC)

AT BE CH DE FR GB IT LI NL

DOCDB simple family (publication)

EP 0199230 A2 19861029; EP 0199230 A3 19880907; EP 0199230 B1 19910109; AT E59893 T1 19910115; DE 3676735 D1 19910214

DOCDB simple family (application)

EP 86105058 A 19860412; AT 86105058 T 19860412; DE 3676735 T 19860412