

Title (en)

DEVICE FOR KEEPING A DOOR OR WINDOW AT LEAST AJAR

Publication

EP 0199270 B1 19930630 (DE)

Application

EP 86105215 A 19860416

Priority

AT 115285 A 19850417

Abstract (en)

[origin: EP0199270A2] To keep a window or door leaf in an ajar position, a housing (2) is fastened to the window or door jamb (1), and in this housing a receiving slot (4) for a catch pin (6) assigned to the leaf (5) is provided and a catch body (10) with at least one catch recess (11) for the catch pin is mounted displaceably, transversely relative to the receiving slot (4), between a locking position and a release position. To ensure a low constructional height, whilst at the same time guaranteeing simple handling, the receiving slot (4) extends parallel to the jamb leg carrying the housing (2) and has an introduction orifice (7) closable by a blocking slide (8) and intended for the catchpin (6) articulated on the leaf by means of a link (19). Furthermore, the catch body (10) is displaceable out of its locking position into its release position counter to the force of a restoring spring (14). <IMAGE>

IPC 1-7

E05C 17/16; E05C 17/28; E05C 17/36; E05C 17/38

IPC 8 full level

E05C 17/16 (2006.01); **E05C 17/28** (2006.01); **E05C 17/36** (2006.01); **E05C 17/38** (2006.01)

CPC (source: EP)

E05C 17/16 (2013.01); **E05C 17/28** (2013.01); **E05C 17/36** (2013.01); **E05C 17/38** (2013.01)

Citation (examination)

DE 1075006 B

Cited by

CN114096727A; EP0208304A3; EP0262347A3; GB2287748A; GB2287748B

Designated contracting state (EPC)

AT DE GB

DOCDB simple family (publication)

EP 0199270 A2 19861029; EP 0199270 A3 19881214; EP 0199270 B1 19930630; AT 384649 B 19871210; AT A115285 A 19870515;
AT E91170 T1 19930715; DE 3688626 D1 19930805

DOCDB simple family (application)

EP 86105215 A 19860416; AT 115285 A 19850417; AT 86105215 T 19860416; DE 3688626 T 19860416