

Title (en)

LABEL SELECTOR FOR FRANKING MACHINES

Publication

EP 0199333 B1 19910320 (FR)

Application

EP 86105516 A 19860422

Priority

FR 8506265 A 19850424

Abstract (en)

[origin: US4652330A] A franking machine has a control lever (7) which is operable between a first position and a second position to cause a slogan to be printed or not to be printed respectively. When said franking machine is being fed with labels, the label selector selects a short label or a long label depending on whether the label is to receive a slogan. The label selector comprises an emitter (E) and a receiver (R) which are mounted in an opto-electronic detector head (41) at a distance from said lever (7) and which are coupled to each other by means of a mirror (42) mounted on the lever (7), but only when the lever is in one of its two specified positions.

IPC 1-7

G07B 17/00

IPC 8 full level

G07B 17/00 (2006.01)

CPC (source: EP US)

G07B 17/00193 (2013.01 - EP US); **G07B 17/00508** (2013.01 - EP US); **G07B 2017/0025** (2013.01 - EP US); **G07B 2017/0062** (2013.01 - EP US)

Cited by

EP0376575A3; US5122967A

Designated contracting state (EPC)

DE FR GB

DOCDB simple family (publication)

EP 0199333 A1 19861029; **EP 0199333 B1 19910320**; DE 3678192 D1 19910425; FR 2581221 A1 19861031; FR 2581221 B1 19870529; US 4652330 A 19870324

DOCDB simple family (application)

EP 86105516 A 19860422; DE 3678192 T 19860422; FR 8506265 A 19850424; US 85525986 A 19860424