

Title (en)

FUEL INJECTION SYSTEM

Publication

EP 0200063 B1 19900117 (EN)

Application

EP 86105077 A 19860414

Priority

US 72890285 A 19850430

Abstract (en)

[origin: EP0200063A1] A bistable fluidic switch (10) is switched from its stable state by a pin (19) inserted in the power nozzle (12) of the bistable fluidic switch (10), the pin (19) being controlled by an electromagnetic actuator (21) which is controlled from an electronic computer (22). The fluidic switch element (10) has a cross-over type interaction region (13) and a common outlet (16) leading to a pair of output passageways (17, 18), one of which (18) returns fuel to the supply tank, and the other of which (17) leads to the air intake manifold of the engine. Air is introduced into the output passageway (17) leading to the engine so as to air atomize the fuel before injection of same into the air intake manifold.

IPC 1-7

F15C 1/04

IPC 8 full level

F02D 41/20 (2006.01); **F02M 51/00** (2006.01); **F02M 51/02** (2006.01); **F02M 51/08** (2006.01); **F02M 69/08** (2006.01); **F15C 1/04** (2006.01);
F15C 1/10 (2006.01)

CPC (source: EP)

F02M 69/08 (2013.01); **F15C 1/04** (2013.01)

Cited by

EP0480329A1; GB2279764A; GB2202000A; FR2655692A1

Designated contracting state (EPC)

DE FR GB IT SE

DOCDB simple family (publication)

EP 0200063 A1 19861105; EP 0200063 B1 19900117; AU 4367189 A 19900208; AU 5646786 A 19861106; AU 589417 B2 19891012;
AU 625562 B2 19920716; BR 8601924 A 19861230; CA 1274130 A 19900918; DE 3668357 D1 19900222; JP H0759920 B2 19950628;
JP S627953 A 19870114

DOCDB simple family (application)

EP 86105077 A 19860414; AU 4367189 A 19891020; AU 5646786 A 19860422; BR 8601924 A 19860429; CA 507961 A 19860430;
DE 3668357 T 19860414; JP 9927386 A 19860428