

Title (en)
PHOTORECEPTOR DRUM FOR ELECTROPHOTOGRAPHY

Publication
EP 0200468 A3 19870121 (EN)

Application
EP 86303059 A 19860423

Priority
JP 9423285 A 19850430

Abstract (en)
[origin: EP0200468A2] A photoreceptor drum for electrophotography comprising a cylindrical conductive substrate (11) and an organic or inorganic photosensitive layer (12) covering the outer surface of said substrate, wherein the maximum roughness, Rmax, of the surface of the photoreceptor drum is in the range of 0.3 S to 2.0 S.

IPC 1-7
G03G 15/00; **G03G 5/00**

IPC 8 full level
G03G 5/02 (2006.01); **G03G 5/10** (2006.01); **G03G 5/14** (2006.01); **G03G 15/00** (2006.01); **G03G 21/10** (2006.01)

CPC (source: EP)
G03G 5/10 (2013.01); **G03G 15/751** (2013.01)

Citation (search report)
• [A] DE 2733187 A1 19780126 - RICOH KK
• [X] PATENT ABSTRACTS OF JAPAN, vol. 8, no. 265 (P-318)[1702], 5th December 1984; & JP-A-59 135 473 (FUJI DENKI SEIZO) 03-08-1984
• [X] PATENT ABSTRACTS OF JAPAN, vol. 6, no. 92 (P-119)[970], 29th May 1982; & JP-A-57 029 051 (FUJI DENKI SEIZO) 16-02-1982
• [XP] PATENT ABSTRACTS OF JAPAN, vol. 9, no. 157 (P-369)[1880], 2nd July 1985; & JP-A-60 033 562 (FUJI DENKI SEIZO) 20-02-1985 (Cat. X)
• [A] PATENT ABSTRACTS OF JAPAN, vol. 8, no. 14 (P-249)[1451], 21st January 1984; & JP-A-58 174 956 (FUJI DENKI SEIZO) 14-10-1983

Cited by
SG90181A1; GB2232264A; US5166023A; GB2232264B; EP0984335A1; EP0730207A1; US5773175A; US6033815A; EP1217452A3; US6474204B1; US6180299B1; US6180300B1; US6258500B1

Designated contracting state (EPC)
DE FR GB NL

DOCDB simple family (publication)
EP 0200468 A2 19861105; **EP 0200468 A3 19870121**; JP S61251859 A 19861108

DOCDB simple family (application)
EP 86303059 A 19860423; JP 9423285 A 19850430