

Title (en)

SECURITY DEVICE FOR WINDOWS WHICH OPEN SELECTIVELY ABOUT A HORIZONTAL OR A VERTICAL AXIS

Publication

EP 0200663 B1 19880720 (FR)

Application

EP 86440023 A 19860325

Priority

FR 8505415 A 19850409

Abstract (en)

[origin: EP0200663A1] 1. Fitting for a window, French window or similar, comprising a security device (1) preventing tampering with the fitting during the opening of the leaf (2) of the window, French window or similar, the fitting comprising at least one operating rod (5) sliding behind a stud (7) housed in a groove and fixed on at least one of the uprights and/or traverses of the leaf (2), the security device (1) comprising a blocking element (13) with a return spring which moves transversally to block the operating rod (5) and whose head (11 2) projects from the outer face (15) of the stud (7), characterized by the fact that the security device (1) comprises an unlocking clapper (14) projecting from the outer face (15) of the stud (7) and which is articulated on a axis (76) situated at the side of the window casing (10), this unlocking clapper (14), parallel to the median plane (34) of the stud (7), being held against the head (64) of the blocking element (13) by an elastic element (81).

IPC 1-7

E05D 15/526

IPC 8 full level

E05D 15/526 (2006.01)

CPC (source: EP)

E05D 15/526 (2013.01); **E05D 2015/5263** (2013.01); **E05Y 2900/148** (2013.01)

Cited by

EP1004735A1; FR2786525A1; WO02075089A1

Designated contracting state (EPC)

AT BE CH DE GB IT LI NL

DOCDB simple family (publication)

EP 0200663 A1 19861105; EP 0200663 B1 19880720; AT E35841 T1 19880815; DE 200663 T1 19870409; DE 3660405 D1 19880825; FR 2580026 A1 19861010; FR 2580026 B1 19891229

DOCDB simple family (application)

EP 86440023 A 19860325; AT 86440023 T 19860325; DE 3660405 T 19860325; DE 86440023 T 19860325; FR 8505415 A 19850409