

Title (en)  
ELECTRICAL CONTACTING DEVICE

Publication  
**EP 0202564 B1 19920916 (DE)**

Application  
**EP 86106394 A 19860512**

Priority  
DE 3518030 A 19850520

Abstract (en)  
[origin: US4750897A] The contact apparatus has at least two contact bodies and at least one segmented body. The latter possesses bars separated from each other by slots and having a curved central area. Furthermore, the bars have the form of a three-dimensional curve. In their end areas, the bars possess in each case a section curved in the opposite sense to said curved central area. Besides, the bars are linked together at their ends by means of edge strips. Moreover, the slots extend up to the curved section. In this way, points of contact clearly defined as regards their position and values are assigned to the convexity as well as the end areas of each bar. These measures lead to an improvement of the mechanical and electrical characteristics of the contact apparatus.

IPC 1-7  
**H01R 13/187; H01R 13/24**

IPC 8 full level  
**H01R 13/11** (2006.01); **H01R 13/187** (2006.01); **H01R 13/24** (2006.01); **H01R 13/02** (2006.01); **H01R 13/115** (2006.01)

CPC (source: EP US)  
**H01R 13/187** (2013.01 - EP US); **H01R 13/02** (2013.01 - EP US); **H01R 13/111** (2013.01 - EP US)

Cited by  
DE102008022695A1; DE102019006851B3; US11411339B2; EP0342385A3; EP0283767A3; CN103836072A; EP2735745A3;  
DE102008024446A1; US9065192B2; WO2010105998A1; WO2015041853A1; EP0716474A1; US8579666B2; EP3800749A1;  
DE102020001379B3; EP3876356A1; US11349245B2; EP3800749B1

Designated contracting state (EPC)  
AT BE CH DE FR GB IT LI LU NL SE

DOCDB simple family (publication)  
**EP 0202564 A2 19861126; EP 0202564 A3 19880727; EP 0202564 B1 19920916**; AT E80754 T1 19921015; CA 1261018 A 19890926;  
DE 3518030 A1 19861120; DE 3518030 C2 19870305; DE 3686736 D1 19921022; JP 2683233 B2 19971126; JP S61279076 A 19861209;  
US 4750897 A 19880614

DOCDB simple family (application)  
**EP 86106394 A 19860512**; AT 86106394 T 19860512; CA 509680 A 19860520; DE 3518030 A 19850520; DE 3686736 T 19860512;  
JP 11712586 A 19860520; US 86344486 A 19860515