

Title (en)

DEVICE FOR HEAT EXCHANGE, ESPECIALLY FOR USE IN GAS HEAT EXCHANGES

Publication

EP 0202981 B1 19890301 (FR)

Application

EP 86400829 A 19860417

Priority

FR 8506297 A 19850423

Abstract (en)

[origin: US4771826A] A heat exchange device is provided whose exchange zone is formed by juxtaposing a plurality of plates parallel with each other and spaced apart two by two by a plurality of spacing elements consisting of spacers parallel to each other, which may be crenellated (they then comprise crenels and projecting parts) or continuous, said plates being formed so that for any two adjacent plates, at least one of the facing faces is provided with spacers, at least one part of said spacers being, over at least a part of their length, in contact with the facing face of the adjacent plate or with at least a part of the spacers possibly present on said facing face, over at least a part of their length, said plates, defining flow spaces for two fluids being further formed and disposed so that for one flow space out of two the spacers carried by at least one of the facing faces of two adjacent plates defining said space are crenellated spacers. The fluids flow advantageous in cross-current relation. The heat exchange devices thus formed, whose plates may be obtained readily by molding (light alloys, thermoplastic materials or thermosetting materials) are advantageously used for exchanges between gases, for example for recovering heat from the smoke of boilers or furnaces.

IPC 1-7

F28F 3/08

IPC 8 full level

F28F 3/04 (2006.01); **F28F 3/08** (2006.01)

CPC (source: EP KR US)

F28D 9/00 (2013.01 - KR); **F28D 9/0037** (2013.01 - EP US); **F28F 3/048** (2013.01 - EP US); **F28F 3/083** (2013.01 - EP US); **F28F 2255/143** (2013.01 - EP); **Y10S 165/392** (2013.01 - EP US); **Y10S 165/905** (2013.01 - EP US); **Y10S 165/906** (2013.01 - EP US)

Cited by

FR2637059A1; FR2637060A1

Designated contracting state (EPC)

DE GB IT NL

DOCDB simple family (publication)

FR 2580794 A1 19861024; **FR 2580794 B1 19890519**; CN 86102864 A 19861029; DE 3662219 D1 19890406; EP 0202981 A1 19861126; EP 0202981 B1 19890301; JP H0565792 B2 19930920; JP S61246597 A 19861101; KR 860008431 A 19861115; KR 940010979 B1 19941121; US 4771826 A 19880920; US 4898233 A 19900206

DOCDB simple family (application)

FR 8506297 A 19850423; CN 86102864 A 19860423; DE 3662219 T 19860417; EP 86400829 A 19860417; JP 9584486 A 19860423; KR 860003117 A 19860423; US 21646688 A 19880707; US 85503486 A 19860423