Title (en)

TILE ELEMENT FIXING MEANS AND TILE ELEMENT COVERING PROVIDED WITH SUCH TILE ELEMENT FIXING MEANS

Publication

EP 0203226 B1 19900321 (EN)

Application

EP 85200859 A 19850529

Priority

EP 85200859 A 19850529

Abstract (en)

[origin: EP0203226A1] Tile covering comprising a number of adjacent tiles (1) being supported by tile supports (6) of elastic material which rest on a roof (4). For fixing of the tiles (1) there are tile fixing means (8) with a circumferentially deformable peripheral element of elastic material which with its peripheral edge (13) cooperates in a clamping manner with an upright edge (7 min) of a tile fixing device accommodation chamber (7) in a tile. For this purpose, the peripheral element (9) cooperates on its inner side with adjacent rigid segments (10a, 10b, 10c, 10d) which are separated from each other and whose internal faces (19) form a tapering surface. Pressing the segments (10a, 10b, 10c, 10d) outwards in order to deform the peripheral element (9), takes place with a disc shaped deformation element (11) having an external surface (18) tapering outwards. In the middle of the disc (11) is a bore (12) provided with screw thread (33) in which a shaft (14) provided with screw thread (13) and having a head (15) can move. When in use, the head (15) of the shaft (14) rests on the bottom (17a) of a tile recess (17) on the top side of the tiles (1). By means of a sockethead screw wrench which is placed in a socket (16) of the head (15) of the shaft, the disc (11) can be moved upwards, said upward movement being limited in each case by top faces (29) connected with the segments and, of course, by the clamping between the segments and the side wall (7) of the accommodation chamber (7). The tile fixing means accommodation chamber (7) can be located on the bottom side of the tile, but it can also be at distance from the bottom in a side wall (23) of the tile (1). The invention also comprises a tile fixing means (8) such as that described above and a tile (1) provided with a tile fixing means accommodation chamber (7), and preferably a recess (17) for accommodation chamber (7), and preferably a recess (17) for accommodation chamber (15) of a shaft (14).

IPC 1-7

E01C 5/00; E04D 11/00; E04F 15/024

IPC 8 full level

E01C 5/00 (2006.01); E04D 11/00 (2006.01); E04F 15/024 (2006.01)

CPC (source: EP)

E01C 5/005 (2013.01); E04D 11/005 (2013.01); E04F 15/02405 (2013.01); E04F 15/02447 (2013.01)

Cited by

FR3128478A1; EP1111132A3; EP1287215A4; ES2326613A1; NL1032369C2; EP1897994A3; DE10022070A1; DE10022070C2; EP1455031A3; EP1143083A1: US7958688B2

EP1143083A1; US/958688B2

Designated contracting state (EPC)

AT BE CH DE FR GB IT LI LU NL SE

DOCDB simple family (publication)

EP 0203226 A1 19861203; EP 0203226 B1 19900321; AT E51265 T1 19900415; DE 3576714 D1 19900426

DOCDB simple family (application)

EP 85200859 A 19850529; AT 85200859 T 19850529; DE 3576714 T 19850529