

Title (en)
DEVICE FOR SHIFTING LOWER BLADES

Publication
EP 0203328 B1 19881026 (DE)

Application
EP 86104893 A 19860410

Priority
DE 3518922 A 19850525

Abstract (en)
[origin: ES8703324A1] The lower cutter of an apparatus for longitudinally slitting a continuous web is mounted for axial displacement along its support shaft to some desired position by the provision of one or more axial first slots provided in the outer periphery of the shaft, a fitting received in each slot underlying the cutter and fastened thereto, and roller bearings between and in contact with the undersurface of the fitting and the bottom of each first slot. One or more second slots are provided in the shaft periphery each receiving a pressure bar bearing against the undersurface of the cutter, and an expandable tube or pillow between the pressure bar and the bottom of the second slot is expanded for fixing the lower cutter in place after axial displacement.

IPC 1-7
B26D 7/26; **B26D 1/40**

IPC 8 full level
B26D 1/24 (2006.01); **B26D 1/40** (2006.01); **B26D 7/26** (2006.01)

CPC (source: EP US)
B26D 1/245 (2013.01 - EP US); **B26D 7/2635** (2013.01 - EP US); **Y10T 83/659** (2015.04 - EP US); **Y10T 83/7826** (2015.04 - EP US); **Y10T 83/7847** (2015.04 - EP US); **Y10T 83/9377** (2015.04 - EP US)

Cited by
WO9111303A1

Designated contracting state (EPC)
BE CH DE FR GB IT LI NL

DOCDB simple family (publication)
EP 0203328 A2 19861203; **EP 0203328 A3 19870225**; **EP 0203328 B1 19881026**; CA 1272120 A 19900731; DE 3518922 A1 19861127; DE 3660989 D1 19881201; ES 555107 A0 19870301; ES 8703324 A1 19870301; JP H0350680 B2 19910802; JP S61274899 A 19861205; US 4646603 A 19870303

DOCDB simple family (application)
EP 86104893 A 19860410; CA 509993 A 19860526; DE 3518922 A 19850525; DE 3660989 T 19860410; ES 555107 A 19860519; JP 11940586 A 19860526; US 86536786 A 19860521