

Title (en)
SUSPENSION OF A GUTTER

Publication
EP 0204368 B1 19900425 (EN)

Application
EP 86200915 A 19860526

Priority
NL 8501559 A 19850531

Abstract (en)
[origin: EP0204368A2] The roof gutter (13) of a building having a slooping roof is suspended by brackets (14; 18) in such a way that a rapid adaptation of the position of the gutter to the thickness of the roof boarding (1, 2, 3) and to the pitch of the roof is permitted, and that leakage water arriving under the tiles, can flow directly into the gutter. Therefore the position and/or length of the brackets (14; 18) is adjustable, and the gutter (13) has such a position under the protruding roof edge that water leakages arriving under the tiles can flow into the gutter.

IPC 1-7
E04D 13/06

IPC 8 full level
E04D 13/072 (2006.01); **E04D 13/17** (2006.01)

CPC (source: EP)
E04D 13/0722 (2013.01); **E04D 13/0725** (2013.01); **E04D 13/178** (2013.01)

Cited by
EP0389058A1; EP0553061A1; WO9718366A1

Designated contracting state (EPC)
AT BE DE FR GB NL SE

DOCDB simple family (publication)
EP 0204368 A2 19861210; EP 0204368 A3 19870909; EP 0204368 B1 19900425; AT E52299 T1 19900515; DE 3670665 D1 19900531; DK 163016 B 19920106; DK 163016 C 19920601; DK 247186 A 19861202; DK 247186 D0 19860527; NL 8501559 A 19861216; NO 166247 B 19910311; NO 166247 C 19910619; NO 862151 L 19861201

DOCDB simple family (application)
EP 86200915 A 19860526; AT 86200915 T 19860526; DE 3670665 T 19860526; DK 247186 A 19860527; NL 8501559 A 19850531; NO 862151 A 19860530