

Title (en)
SETTING-UP DEVICE OF AN IMPERVIOUS MULTILAYERED COATING

Publication
EP 0204602 B1 19881102 (FR)

Application
EP 86401066 A 19860520

Priority
FR 8507728 A 19850522

Abstract (en)
[origin: EP0204602A1] 1. A method of putting in place a sealing covering, more particularly for roofs, terraces or constructional works such as bridges, comprising at least two layers superimposed on a surface of a support (S) to be protected, the first layers (1) of the covering, close to the surface to be protected, being formed by at least one bituminous sheet (2) comprising on its surface oriented towards the support, or lower surface, a screen (8) formed with openings (10) and made from a material which cannot be degraded by heat up to a temperature of about 200 degrees C but can be so degraded by the application of a flame, characterized in that the surface of the support to be protected is covered with at least one of the bituminous sheets (2) to form the lower layer of the covering in such a way that the screen (8) of the sheet is opposite the surface to be protected, and a second layer (3) is so glued hot to the lower layer that the heat generated during the putting in place of the second layer procudes glueing to the surface of the sheet (2) to be protected by the adhesion to the support of the bituminous composition of the sheet (2) via at least some of the openings (10) with which the screen (8) is formed.

IPC 1-7
E04D 5/12

IPC 8 full level
E04D 5/12 (2006.01)

CPC (source: EP)
E04D 5/12 (2013.01)

Cited by
CN108646681A; FR2708303A1; FR2706506A1; FR2680532A1

Designated contracting state (EPC)
AT BE CH DE FR GB IT LI LU NL SE

DOCDB simple family (publication)
EP 0204602 A1 19861210; EP 0204602 B1 19881102; AT E38406 T1 19881115; DE 3661087 D1 19881208; FR 2582333 A1 19861128; FR 2582333 B1 19890818

DOCDB simple family (application)
EP 86401066 A 19860520; AT 86401066 T 19860520; DE 3661087 T 19860520; FR 8507728 A 19850522