

Title (en)

WORK PIECE THICKNESS DETECTOR FOR A SEWING MACHINE

Publication

EP 0205377 B1 19900411 (FR)

Application

EP 86401166 A 19860602

Priority

FR 8508317 A 19850603

Abstract (en)

[origin: ES8704220A1] A device for detecting a thickness variation of a piece of fabric passing under the presser foot of a sewing machine. The device includes a transmitter and receiver between which the fabric passes. The receiver stores maximum and minimum signals in memory units generated when the fabric passes between the transmitter and receiver. A computing unit calibrates the thresholds as a function of the stored maximum and minimum signals. A comparator compares the incoming signals with the calibrated thresholds and sends a signal to a logic unit to control the sewing operations accordingly.

IPC 1-7

D05B 35/10; G01B 11/02; G01B 11/06

IPC 8 full level

D05B 69/00 (2006.01); D05B 35/10 (2006.01); D05B 69/24 (2006.01); G01B 11/02 (2006.01); G01B 11/06 (2006.01)

CPC (source: EP KR US)

D05B 69/22 (2013.01 - KR); D05B 69/24 (2013.01 - EP US)

Cited by

DE3905482A1; EP1777331A1; DE3934933A1; GB2215835A; US4962569A; DE3843073A1

Designated contracting state (EPC)

AT BE CH DE GB IT LI LU NL SE

DOCDB simple family (publication)

EP 0205377 A1 19861217; EP 0205377 B1 19900411; AT E51905 T1 19900415; BR 8602541 A 19870203; CA 1273427 A 19900828; DE 3670318 D1 19900517; ES 555660 A0 19870316; ES 8704220 A1 19870316; FR 2582683 A1 19861205; FR 2582683 B1 19880527; IL 78945 A0 19860930; IL 78945 A 19891215; JP H0234633 B2 19900806; JP S61279296 A 19861210; KR 870000473 A 19870218; PT 82698 A 19860701; PT 82698 B 19920731; US 4829194 A 19890509

DOCDB simple family (application)

EP 86401166 A 19860602; AT 86401166 T 19860602; BR 8602541 A 19860602; CA 510608 A 19860602; DE 3670318 T 19860602; ES 555660 A 19860603; FR 8508317 A 19850603; IL 7894586 A 19860527; JP 12739586 A 19860603; KR 860004396 A 19860603; PT 8269886 A 19860603; US 86987486 A 19860603