

Title (en)
IMAGE CONTROLLING METHOD AND DEVICE FOR CARRYING OUT THE SAME

Publication
EP 0205726 A3 19890510 (EN)

Application
EP 86100265 A 19860110

Priority
JP 12351085 A 19850608

Abstract (en)
[origin: EP0205726A2] An image controlling method and a device for carrying out the same, for shifting a processing position indicating point displayed on a CRT, for example, of a computerized game, in response to the variation of an image displayed on the CRT, by selectively closing one or two switches among a plurality of switches (3) disposed at equal angular intervals around and at the same distance from a fixed point corresponding to the center of a control disk (4). The control disk (4) is inclined in a desired direction by applying a light pressure with the hand to a generally spherical operating ball (7) which fits the palm of the hand snug so that the switch or switches corresponding to the desired direction are closed.

IPC 1-7
H01H 25/04

IPC 8 full level
G06F 3/0338 (2013.01); **H01H 25/04** (2006.01); **G05G 9/047** (2006.01)

CPC (source: EP)
G05G 9/047 (2013.01); **H01H 25/04** (2013.01); **G05G 2009/04711** (2013.01); **G05G 2009/04744** (2013.01)

Citation (search report)
• [X] EP 0024813 A1 19810311 - ATARI INC [US]
• [Y] DE 1268251 B 19680516 - SIEMENS AG
• [A] WO 8403051 A1 19840816 - AMIGA CORP [US]
• [A] DE 2810609 A1 19780914 - ATARI INC
• [A] I.B.M. TECHNICAL DISCLOSURE BULLETIN vol. 26, no. 7B, December 1983, New York page 3746 - 3747; R.W.Truelson: "Single-Key Cursor Control"

Cited by
GB2215132A; GR1000072B; US5473325A; US5589828A; GB2229316A; GB2229316B; US5638062A; EP0452233A1; FR2661037A1; WO8907829A3; WO9318475A1

Designated contracting state (EPC)
DE FR GB IT NL

DOCDB simple family (publication)
EP 0205726 A2 19861230; EP 0205726 A3 19890510; EP 0205726 B1 19920617; DE 3685690 D1 19920723; DE 3685690 T2 19930513; JP S61292734 A 19861223

DOCDB simple family (application)
EP 86100265 A 19860110; DE 3685690 T 19860110; JP 12351085 A 19850608