

Title (en)

MEANS FOR FRICTION SPINNING IN A FRICTION SPINNING APPARATUS

Publication

EP 0206198 B1 19910821 (DE)

Application

EP 86108187 A 19860616

Priority

DE 3521665 A 19850618

Abstract (en)

[origin: US4696155A] A friction spinning device has a pneumatic fiber transport passage or channel inclined at an angle to a perforated friction spinning element and a yarn formation position of the perforated friction spinning element is located at a spacing from an opening of the pneumatic fiber transport passage or channel. In such a friction spinning device, it is desired to ensure that the fibers located on the perforated friction spinning element are transported towards the yarn formation position neither parallel to nor at right angles to the yarn formation position. For this purpose, the perforations of the perforated friction spinning elements are so arranged that straight lines joining the perforation centers are disposed neither parallel to nor at right angles to the yarn formation position. In this way, fibers transported onto the perforated friction spinning element are laid on such perforated friction spinning element in the direction of the rows of perforations due to the intensity of the transporting air. In this way, a desired or appropriate disposition of these fibers is ensured.

IPC 1-7

D01H 4/16

IPC 8 full level

D01H 4/16 (2006.01); **D01H 4/18** (2006.01)

CPC (source: EP US)

D01H 4/16 (2013.01 - EP US); **D01H 4/18** (2013.01 - EP US)

Cited by

DE3832110A1; US4938018A

Designated contracting state (EPC)

CH DE FR GB IT LI

DOCDB simple family (publication)

EP 0206198 A2 19861230; EP 0206198 A3 19880127; EP 0206198 B1 19910821; DE 3521665 A1 19870102; DE 3680958 D1 19910926; IN 167332 B 19901006; JP S6228413 A 19870206; US 4696155 A 19870929

DOCDB simple family (application)

EP 86108187 A 19860616; DE 3521665 A 19850618; DE 3680958 T 19860616; IN 281MA1986 A 19860416; JP 11939986 A 19860526; US 87452286 A 19860616