

Title (en)

METHOD AND APPARATUS FOR OPEN-END FRICTION SPINNING

Publication

EP 0208114 B1 19890705 (DE)

Application

EP 86107209 A 19860527

Priority

DE 3524942 A 19850712

Abstract (en)

[origin: US4727716A] To improve integration of fibers into a yarn end and thereby improve yarn quality, fibers are directed to a feeding nip defined on an opposite side of a pair of friction rollers forming a spinning nip. The fibers are directed out of the feeding nip, passed between the friction rollers, and forwarded into the spinning nip. One of the friction rollers may constitute a conveying roller which exerts greater force upon the fibers than the other roller to securely convey fibers through a gap between the rollers and into the spinning nip.

IPC 1-7

D01H 1/135

IPC 8 full level

D01H 4/16 (2006.01); **D01H 4/18** (2006.01); **D01H 4/38** (2006.01)

CPC (source: EP US)

D01H 4/16 (2013.01 - EP US)

Cited by

EP0278604A1

Designated contracting state (EPC)

CH DE FR GB IT LI

DOCDB simple family (publication)

EP 0208114 A2 19870114; EP 0208114 A3 19871028; EP 0208114 B1 19890705; BR 8603120 A 19870217; CN 86104572 A 19870107; DE 3524942 A1 19870122; DE 3524942 C2 19881215; DE 3664220 D1 19890810; IN 167803 B 19901222; JP H0236687 B2 19900820; JP S6215334 A 19870123; US 4727716 A 19880301

DOCDB simple family (application)

EP 86107209 A 19860527; BR 8603120 A 19860703; CN 86104572 A 19860711; DE 3524942 A 19850712; DE 3664220 T 19860527; IN 598MA1986 A 19860728; JP 15812086 A 19860707; US 88224186 A 19860707