

Title (en)

Tight receptacle.

Title (de)

Abgedichteter Behälter.

Title (fr)

Réceptient étanche.

Publication

**EP 0212504 A2 19870304 (EN)**

Application

**EP 86111002 A 19860808**

Priority

JP 12487585 U 19850814

Abstract (en)

A tight receptacle having a gasket (12) between a body (2) and a closure (4), characterized in which either the body or the closure having a pair of shafts (14) at the opposite sides thereof for pivoting a pair of rotary locking members (6), the other having a pair of projections (8) at vertically downward positions with respect to the shafts when the closure is put on the body, the locking members (6) having cam grooves (20) consisting of external cams (34) and an internal cams (40), the external cams comprising lobes (32) for expanding between the shafts and the projections, and the internal cams comprising lobes (36) for narrowing between the shafts and the projections.

IPC 1-7

**B65D 45/18**; **B65D 45/20**

IPC 8 full level

**B65D 43/02** (2006.01); **B65D 45/18** (2006.01); **B65D 45/20** (2006.01); **B65D 77/20** (2006.01)

CPC (source: EP)

**B65D 45/18** (2013.01); **B65D 45/20** (2013.01)

Cited by

EP0265329A1; FR2621559A2; WO02051713A1

Designated contracting state (EPC)

DE FR GB IT

DOCDB simple family (publication)

**EP 0212504 A2 19870304**; **EP 0212504 A3 19880824**; **EP 0212504 B1 19891129**; DE 3667156 D1 19900104; JP H0417495 Y2 19920420; JP S6233555 U 19870227

DOCDB simple family (application)

**EP 86111002 A 19860808**; DE 3667156 T 19860808; JP 12487585 U 19850814