

Title (en)
Posterior sealing of waste deposits.

Title (de)
Nachträgliche Deponieabdichtung.

Title (fr)
Etanchement postérieure de décharges.

Publication
EP 0213259 A2 19870311 (DE)

Application
EP 86100839 A 19860122

Priority
DE 3531183 A 19850831

Abstract (en)
1. A method of subsequently sealing waste dumps and/or contaminated areas, wherein a seal is introduced beneath the dump and/or contaminated area by pulling-in profile strips (1, 2) in succession, each profile strip (1, 2) becoming connected directly with the previously introduced profile strips as it is pulled in, characterized in that, in the pulling-in or pushing-in of the successive profile strips (1, 2), the soil opposing the pulling-in or pushing-in is at least partly excavated.

Abstract (de)
Nach der Erfindung wird zum Einbringen von Profilsträngen (1) unterhalb einer Deponie für jeden Profilstrang (1) eine Erdbohrung (5) hergestellt und das dabei gewonnene Material durch den Profilstrang (1) bzw. den vorher gelegten Profilstrang (1) abgefördert.

IPC 1-7
E02D 31/00

IPC 8 full level
E02D 31/00 (2006.01); **E02F 5/18** (2006.01)

CPC (source: EP)
E02D 31/006 (2013.01)

Cited by
EP0328608B1

Designated contracting state (EPC)
AT BE CH DE FR GB IT LI NL SE

DOCDB simple family (publication)
EP 0213259 A2 19870311; **EP 0213259 A3 19880210**; **EP 0213259 B1 19900905**; AT E56235 T1 19900915; DE 3531183 A1 19870312; DE 3673921 D1 19901011

DOCDB simple family (application)
EP 86100839 A 19860122; AT 86100839 T 19860122; DE 3531183 A 19850831; DE 3673921 T 19860122