

Title (en)
APPLICATION METHOD AND APPLICATION DEVICE

Publication
EP 0213323 B1 19891011 (EN)

Application
EP 86109111 A 19860703

Priority
JP 14712385 A 19850704

Abstract (en)
[origin: EP0213323A2] In an application method and an application device, a liquid (3) to be applied is supplied to form a liquid reservoir (8) immediately upstream of the contact portion between a rotating bar (1) and a continuously-moving web (2) so as to apply the liquid (3) to the web (2). The effective application length of the bar (1) is set to be shorter than the width of the web (2) so as to prevent the liquid (3) from flying away and suction openings (11) are provided at both the end faces (10) of the effective application length part of the bar (1) so as to suck the excess portion of the liquid (3) along the end faces (10) of the bar (1).

IPC 1-7
B05C 1/08; **B05D 1/28**; **G03C 1/74**

IPC 8 full level
B05C 1/08 (2006.01); **B05C 1/12** (2006.01); **B05C 5/02** (2006.01); **B05C 11/02** (2006.01); **B05C 11/04** (2006.01); **B05C 11/10** (2006.01); **B05D 1/28** (2006.01); **G03C 1/74** (2006.01)

CPC (source: EP)
B05C 1/0826 (2013.01); **B05C 1/12** (2013.01); **B05C 11/1039** (2013.01); **B05D 1/28** (2013.01); **G03C 1/74** (2013.01)

Cited by
EP0376207A3; EP1214987A3; CN114901401A; EP0768118A1; US5820935A

Designated contracting state (EPC)
DE NL

DOCDB simple family (publication)
EP 0213323 A2 19870311; **EP 0213323 A3 19871104**; **EP 0213323 B1 19891011**; DE 3666151 D1 19891116; JP H0582271 B2 19931118; JP S627467 A 19870114

DOCDB simple family (application)
EP 86109111 A 19860703; DE 3666151 T 19860703; JP 14712385 A 19850704