

Title (en)  
CONNECTOR FOR PRINTED CIRCUIT BOARDS

Publication  
**EP 0213446 B1 19920129 (DE)**

Application  
**EP 86110867 A 19860806**

Priority  
DE 3528912 A 19850812

Abstract (en)  
[origin: US4717344A] A daughterboard connector (6) has a polarity key formed by two walls (14, 15) on either side of a recess (12). A lateral contact (8) mounted in the recess engages a bus bar (3, 4) which is mounted in a pair of slots (20) in the end of a motherboard connector (11). A flange (7) adjacent one of the slots forms a polarity key for the motherboard connector. The height and positioning of the lateral contact and the bus bar are chosen to provide a first-make-last-break function for these elements relative to the signal contacts 19 and 16 of the daughterboard and motherboard connectors, respectively. The bus bar (3, 4) may be common to a number of motherboard connectors which are mounted on a common printed circuit board.

IPC 1-7  
**H01R 23/68**

IPC 8 full level  
**H01R 12/16** (2006.01); **H01R 12/18** (2006.01); **H01R 12/70** (2011.01)

CPC (source: EP US)  
**H01R 12/7088** (2013.01 - EP US)

Cited by  
EP0674812A4

Designated contracting state (EPC)  
BE DE FR GB IT NL SE

DOCDB simple family (publication)  
**EP 0213446 A2 19870311; EP 0213446 A3 19890222; EP 0213446 B1 19920129**; DE 3528912 A1 19870219; DE 3528912 C2 19880407; DE 3683706 D1 19920312; SG 37294 G 19941028; US 4717344 A 19880105

DOCDB simple family (application)  
**EP 86110867 A 19860806**; DE 3528912 A 19850812; DE 3683706 T 19860806; SG 37294 A 19940312; US 89441286 A 19860807