

Title (en)
POSITIVE DISPLACEMENT MACHINE, PARTICULARLY PUMP

Publication
EP 0214164 B1 19900523 (DE)

Application
EP 86901030 A 19860221

Priority
CH 89485 A 19850227

Abstract (en)
[origin: WO8605241A1] The machine comprises two plate-like supports (9, 12) each provided with a crown of displacement blades (10), respectively displacement chambers (11), engaged into each other, and displaceable into a relative circular translation motion. The drive is implemented by a gear (7-9) at the center of the supports (9, 12), which exerts a force (FN) on one of the supports (9) at a radially displaceable position, said force presenting a radial component (FR) and a tangential component (FT). The direction of the force and the arrangement of the chambers (11) are so selected as to provide for a predetermined static position of the blades (10) in the chambers (11) independently of the wear. Optimum operation conditions are thus obtained with simple design and fabrication. For producing said pump, the plate-like supports are lapped pair-wise when they are in the state of blanks in conditions similar to the operation conditions and are then mounted in the machine .

IPC 1-7
F04C 2/04; F04C 15/00

IPC 8 full level
F01C 17/00 (2006.01); **F04C 2/04** (2006.01); **F04C 15/00** (2006.01); **F04C 18/04** (2006.01)

CPC (source: EP US)
F01C 17/00 (2013.01 - EP US); **F04C 2/04** (2013.01 - EP US); **F04C 15/0023** (2013.01 - EP US); **F04C 15/0046** (2013.01 - EP US); **F04C 15/0065** (2013.01 - EP US)

Citation (examination)
DE 2230773 A1 19730620 - AGINFOR AG

Designated contracting state (EPC)
CH DE FR GB IT LI SE

DOCDB simple family (publication)
WO 8605241 A1 19860912; BR 8605494 A 19870422; DE 3671503 D1 19900628; EP 0214164 A1 19870318; EP 0214164 B1 19900523; JP 2771160 B2 19980702; JP S62501982 A 19870806; US 4789315 A 19881206

DOCDB simple family (application)
CH 8600023 W 19860221; BR 8605494 A 19860221; DE 3671503 T 19860221; EP 86901030 A 19860221; JP 50102186 A 19860221; US 92817786 A 19861201