

Title (en)

METHOD AND DEVICE FOR REMOVING THE RESPECTIVE UPPERMOST LAYER OF A STACK FORMED OF FABRIC PLIES

Publication

**EP 0214576 B1 19900117 (DE)**

Application

**EP 86112019 A 19860830**

Priority

NL 8502400 A 19850902

Abstract (en)

[origin: ES2001630A6] Processes for removing the top ply from a stack of plies, such as layers of fabric, in which an element engages the stack and moves relative to the ply to be removed along the face of said ply while pressure is inserted by the element on the stack in such a way that this is locally dented. The element used to engage the ply is provided with a smooth surface. The invention also relates to a device for carrying out this method having a single hollow element which is provided with suction openings or blow openings and can be moved perpendicular to its longitudinal axis.

IPC 1-7

**A41H 43/02; B65H 3/14**

IPC 8 full level

**B65H 3/08** (2006.01); **B65H 3/14** (2006.01); **B65H 3/22** (2006.01); **B65H 3/60** (2006.01)

CPC (source: EP KR US)

**A41H 43/00** (2013.01 - KR); **B65H 3/14** (2013.01 - EP US); **B65H 3/22** (2013.01 - EP US)

Cited by

US4824321A; WO9114641A1

Designated contracting state (EPC)

BE DE FR GB IT LU NL

DOCDB simple family (publication)

**EP 0214576 A1 19870318; EP 0214576 B1 19900117**; BR 8604180 A 19870428; DE 3668309 D1 19900222; ES 2001630 A6 19880601; JP S62126054 A 19870608; KR 870002785 A 19870413; NL 8502400 A 19870401; US 4802662 A 19890207

DOCDB simple family (application)

**EP 86112019 A 19860830**; BR 8604180 A 19860901; DE 3668309 T 19860830; ES 8601544 A 19860901; JP 20525986 A 19860902; KR 860007311 A 19860902; NL 8502400 A 19850902; US 90260886 A 19860902