

Title (en)  
DEVICE FOR TRIBOLOGIC MEASUREMENTS

Publication  
**EP 0214687 A3 19871111 (EN)**

Application  
**EP 86201477 A 19860828**

Priority  
IT 2207685 A 19850906

Abstract (en)  
[origin: EP0214687A2] In a device for tribologic measurements between a first revolving piece and a second piece insisting on the first one, wherein the friction force between the two pieces is detected by a dynamometer, provision is made for constraining the second component to the revolution axis of the first component, to avoid that tangential displacements of the two pieces relatively to each other, which could cause the contact areas to vary, may occur.

IPC 1-7  
**G01N 3/24**; **G01N 19/02**; **G01N 3/56**

IPC 8 full level  
**G01N 3/56** (2006.01); **G01N 19/02** (2006.01)

CPC (source: EP)  
**G01N 3/56** (2013.01); **G01N 19/02** (2013.01)

Citation (search report)  
• [A] FR 2277342 A1 19760130 - FRANCE ETAT [FR]  
• [A] DE 1473679 A1 19690102 - AGFA GEVAERT AG  
• [A] REVIEW OF SCIENTIFIC INSTRUMENTS, vol. 55, no. 6, June 1984, pages 998-1000, New York, US; S. KALACHANDRA et al.: "Friction tester for the lubrication properties of ophthalmic solutions"

Cited by  
GB2187560B; DE4324620A1; DE19700089A1; DE19700089C2; GB2435794A; EP0497263A1; US5343733A; GB2435794B; JP2015215236A; WO2006072760A1

Designated contracting state (EPC)  
BE DE FR GB IT LU NL

DOCDB simple family (publication)  
**EP 0214687 A2 19870318**; **EP 0214687 A3 19871111**; IT 1214630 B 19900118; IT 8522076 A0 19850906

DOCDB simple family (application)  
**EP 86201477 A 19860828**; IT 2207685 A 19850906