

Title (en)  
SWITCHING MAT AND PROCESS FOR ITS MANUFACTURE

Publication  
**EP 0215037 B1 19890816 (DE)**

Application  
**EP 86901354 A 19860303**

Priority  
DE 3507922 A 19850306

Abstract (en)  
[origin: WO8605317A1] The switching mat consists of two, facing, electrically conductive contact surfaces (1, 2) which are movable the one against the other. Between these are contact windows (4) in electrically-insulated buffer elements (3) the latter being perpendicular to the contact surfaces and elastically ductile. In the area of the contact windows (4), jutting contact nobs (5) are provided on at least one of the two contact surfaces (1, 2), with the distance between contact nobs (5) and the opposite contact surfaces (1, 2) (or the opposite contact nobs) when the switching mat is not charged being not greater than the elastic spring stroke of the buffer elements (3). The contact nobs (5) can be formed of bulges in a film forming one of the contact surfaces (1, 2). To produce the bulges, a difference in pressure is built up between the inside and outside of the switching mat after the sides of both contact surfaces (1, 2) have been sealed, so that bulges are formed in the area of the contact windows (4) on the inside. The bulges are fixed by means of a hardening layer of sufficient form rigidity applied to the outside.

IPC 1-7  
**H01H 3/14**

IPC 8 full level  
**H01H 3/14** (2006.01)

CPC (source: EP US)  
**H01H 3/141** (2013.01 - EP US); **Y10T 29/49105** (2015.01 - EP US)

Designated contracting state (EPC)  
AT BE CH FR GB IT LI NL SE

DOCDB simple family (publication)  
**WO 8605317 A1 19860912**; DE 3507922 A1 19860911; DE 3507922 C2 19871008; EP 0215037 A1 19870325; EP 0215037 B1 19890816; US 4773155 A 19880927

DOCDB simple family (application)  
**DE 8600079 W 19860303**; DE 3507922 A 19850306; EP 86901354 A 19860303; US 93352386 A 19861105