

Title (en)

SCINTILLATOR INPUT SCREEN FOR AN X-RAY IMAGE INTENSIFIER, AND METHOD OF MANUFACTURING SUCH A SCINTILLATOR

Publication

EP 0215699 B1 19890621 (FR)

Application

EP 86401835 A 19860819

Priority

FR 8512688 A 19850823

Abstract (en)

[origin: US4803366A] The present invention provides an input screen scintillator for a radiological image intensifier tube in which the cesium iodide needles of the scintillator are coated with a refractory, transparent or reflecting, material having an optical index close to or less than that of the cesium iodide. Different methods may be used for coating, such as chemical vapor phase deposition, activated by thermal excitation, plasma excitation or photonic excitation; or such as diffusion deposition of a colloidal solution; or such as polymerization of a polymer resin. After coating, is realized the heat treatment which ensures the luminescence of the screen.

IPC 1-7

H01J 9/12; H01J 29/38

IPC 8 full level

G21K 4/00 (2006.01); **C09K 11/00** (2006.01); **G01T 1/20** (2006.01); **H01J 9/12** (2006.01); **H01J 9/22** (2006.01); **H01J 29/38** (2006.01);
H01J 31/50 (2006.01)

CPC (source: EP US)

H01J 9/12 (2013.01 - EP US); **H01J 29/385** (2013.01 - EP US)

Citation (examination)

"Handbook of Optics", Mc Graw-Hill Book Comp., (1978)

Cited by

EP0413482A3; DE10116803A1; DE10116803C2; EP0372395A3; US5083017A; EP0352152A1; FR2634562A1; US4985633A; EP0325500A1;
FR2625838A1; US4980561A; US5298294A

Designated contracting state (EPC)

DE GB NL

DOCDB simple family (publication)

EP 0215699 A1 19870325; EP 0215699 B1 19890621; DE 3664079 D1 19890727; FR 2586508 A1 19870227; FR 2586508 B1 19880826;
JP 2571771 B2 19970116; JP S6273538 A 19870404; US 4803366 A 19890207

DOCDB simple family (application)

EP 86401835 A 19860819; DE 3664079 T 19860819; FR 8512688 A 19850823; JP 19646086 A 19860821; US 89793886 A 19860819