

Title (en)

Electromagnetic actuator, in particular for driving print hammers.

Title (de)

Elektromagnetische Betätigungsvorrichtung, insbesondere für Druckhammerantriebe.

Title (fr)

Dispositif d'actionnement électromagnétique notamment de marteaux d'impression.

Publication

**EP 0216943 A1 19870408 (DE)**

Application

**EP 85109847 A 19850806**

Priority

EP 85109847 A 19850806

Abstract (en)

1. Electromagnetic actuator mechanism for switching, stroke or impact motions, comprising a clapper armature (1) and an electromagnet (2) consisting of an excitation coil (3) and a magnetizable yoke structure (4), wherein the clapper armature is attracted by the yoke structure upon excitation of the electromagnet, characterized in that the yoke structure has a substantially E-shaped cross-section with two outer legs (5, 6), one center leg (7) and a base (8) common to all legs, and said cross-section lies in the magnetic flux plane, wherein the pole face (7A) of the center leg (7), encompassed by the excitation coil (3), faces the clapper armature (1), and the free ends of the outer legs are so bent in a direction towards each other that a magnetic operating gap (9) is formed between their pole faces (5A, 6A), outside or inside of which the pole face (7A) of the center leg (7) is positioned, the motional plane (1A) of the clapper armature (1) extends perpendicularly to the plane (4A) of the magnetic flux (4B) of the yoke structure (4) of the electromagnet, upon excitation of the electromagnet (2), the clapper armature (1) is pulled inside the operating gap (9) in a known manner by the forces occurring between its pole faces (5A, 6A) and the clapper armature, and in the process, the clapper armature (1) is increasingly attracted by the pole face (7A) of the center leg (7), with substantially half of the magnetic flux of the center leg passing across the clapper armature (1) to one pole face (5A, 6A) of the operating gap (9), and the length of the clapper armature (1) between its pivotal axis (10) and the operating gap (9) is more than twice the width of the clapper armature (1) between the pole faces (5A, 6A) of the operating gap (9).

Abstract (de)

Ein Schwenkanker (1) wird bei Erregung des Elektromagneten (3, 4) in einen Arbeitsspalt (9) gezogen, wobei er in zunehmendem Maße zusätzlich von dem Pol (7A) eines Elektromagnetjochschenkels (7) angezogen wird. Die Bewegungsebene (1A) des Schwenkankers (1) verläuft senkrecht zur Ebene (4A) des Magnetflusses (4B) der Jochstruktur (4) des Elektromagneten.

IPC 1-7

**H01F 7/08**

IPC 8 full level

**B41J 2/275** (2006.01); **H01F 7/08** (2006.01)

CPC (source: EP)

**H01F 7/081** (2013.01)

Citation (search report)

- [X] DE 1900131 A1 19690904 - HONEYWELL INC
- [A] DE 2433775 A1 19750528 - ELEKTRO APP WERKE VEB
- [A] US 2348556 A 19440509 - MATTHIAS LYNN H
- [A] US 2999193 A 19610905 - WILHELM BREITLING
- [A] DE 3024059 A1 19820107 - KNORR BREMSE GMBH [DE]
- [A] DE 2458516 A1 19760616 - TEVES GMBH ALFRED
- [A] FR 1236085 A 19600715

Cited by

EP0778592A3; FR2801721A1; EP1103989A3; WO9641947A1

Designated contracting state (EPC)

BE CH DE FR GB IT LI NL SE

DOCDB simple family (publication)

**EP 0216943 A1 19870408; EP 0216943 B1 19891102;** AR 242683 A1 19930430; BR 8603482 A 19870304; CA 1249625 A 19890131;  
DE 3574072 D1 19891207; ES 297044 U 19880416; ES 297044 Y 19881201; JP H0533666 B2 19930520; JP S6235857 A 19870216

DOCDB simple family (application)

**EP 85109847 A 19850806;** AR 30481186 A 19860806; BR 8603482 A 19860724; CA 503282 A 19860304; DE 3574072 T 19850806;  
ES 297044 U 19860617; JP 15812786 A 19860707