

Title (en)
LIFTING JACK

Publication
EP 0216959 B1 19900117 (EN)

Application
EP 85201589 A 19851001

Priority
EP 85201589 A 19851001

Abstract (en)
[origin: EP0216959A1] The invention aims at obtaining a mechanical lifting jack of minimum height and in which friction on rotation of the rotating parts is low even under high load. The lifting jack comprises a rigid body (17) defining a cylindrical ram passage (41) and a planar base (28). A cylindrical plate (83) rests above the interior surface of base (28) and supports a beveled gear (27). A threaded screw bar (14) is attached to beveled gear (27) and extends upwardly therefrom. A threaded sleeve (21) is received by screw base (14) and supports a ram (16). The latter is movable within ram passage (41) and terminates in a load bearing head (10). A pinion gear (90) is supported in engagement with beveled gear (27) and is coupled to a conventional ratchet drive (92). A sliding pad (29) formed of a layer of a fluorine resin material having a low frictional coefficient and self-lubricating property, is interposed between plate (83) and base (28) to act as a bearing for beveled gear (27).

IPC 1-7
B66F 3/08; **B66F 3/16**

IPC 8 full level
B66F 3/08 (2006.01); **B66F 3/16** (2006.01)

CPC (source: EP)
B66F 3/08 (2013.01); **B66F 3/16** (2013.01)

Cited by
CN102515052A; EP0754527A1; CN108840269A; AU678742B2; CN104803320A

Designated contracting state (EPC)
DE FR IT NL

DOCDB simple family (publication)
EP 0216959 A1 19870408; **EP 0216959 B1 19900117**; DE 3575411 D1 19900222

DOCDB simple family (application)
EP 85201589 A 19851001; DE 3575411 T 19851001