

Title (en)  
**ARTICULATED BRACELET**

Publication  
**EP 0217016 B1 19890517 (FR)**

Application  
**EP 86109495 A 19860711**

Priority  
CH 419385 A 19850927

Abstract (en)  
[origin: EP0217016A1] 1. Articulated bracelet, particularly for a watch, comprising small bars (1, 2) disposed parallel with one another and at right angles to the longitudinal axis of the bracelet, and connecting elements (5) adapted to connect one bar to an adjacent bar while remaining free to pivot about the axes of the bars, characterized in that each of the said elements is formed by two substantially flat hooks (6, 7) and a bridge (8) connecting the two hooks together, each hook, which constitutes one of the two ends of the said element, being provided with a transverse hole (9, 10) the axis of which is at right angles to the plane of the hook, the said hole ending at the outside in the form of a lateral slot (11, 12), disposed at a right angle to the straight line connecting the centres of the holes, the width of the slot being less than the diameter of the hole so that each end of the said element can be engaged by force, by resilient deformation of the corresponding hook, in groove (3, 4) of revolution provided in each bar, the diameter of the groove being equal to the diameter of the hole in the hook.

IPC 1-7  
**A44C 5/10**

IPC 8 full level  
**A44C 5/10** (2006.01)

CPC (source: EP)  
**A44C 5/107** (2013.01)

Cited by  
JP2020080983A; US6921800B2; US7211537B2

Designated contracting state (EPC)  
AT DE FR GB IT

DOCDB simple family (publication)  
**EP 0217016 A1 19870408; EP 0217016 B1 19890517**; AT E43050 T1 19890615; CH 663709 A5 19880115; DE 3663324 D1 19890622

DOCDB simple family (application)  
**EP 86109495 A 19860711**; AT 86109495 T 19860711; CH 419385 A 19850927; DE 3663324 T 19860711