

Title (en)

LIGHTING FIXTURE AND METHOD OF LIGHTING

Publication

EP 0217323 A3 19890308 (DE)

Application

EP 86113329 A 19860927

Priority

DE 3535216 A 19851002

Abstract (en)

[origin: EP0217323A2] Lighting fixture for direct and indirect lighting for a room or area of a room in a building or the like. Arranged in the lighting fixture housing is at least one reflector opposite whose reflecting topside, which is directed towards the upper light exit aperture of the lighting fixture, at least one lamp of this lighting fixture is arranged. A lower light exit aperture having a transparent lower cover which diffusely scatters the light is present on the underside of the housing. A small proportion of the useful light flux that can be emitted by the at least one lamp of this lighting fixture can be emitted through the lower light exit aperture, this lighting fixture thereby causing fewer interfering reflexes on parts of work places or the like which it illuminates and which reflect specularly. <IMAGE>

IPC 1-7

F21V 7/00; F21S 3/02

IPC 8 full level

F21S 8/06 (2006.01); **F21V 7/00** (2006.01); **F21V 11/14** (2006.01)

CPC (source: EP US)

F21S 8/06 (2013.01 - EP US); **F21V 7/0016** (2013.01 - EP); **F21V 11/14** (2013.01 - EP); **F21Y 2103/00** (2013.01 - EP US)

Citation (search report)

- [X] US 4472767 A 19840918 - WENMAN JAMES A [US]
- [X] US 4450513 A 19840522 - GUGGEMOS ARTHUR R [US]
- [A] US 4280170 A 19810721 - BALDWIN SAMUEL L
- [A] US 3201582 A 19650817 - SIEGEL AL L
- [A] DE 3318264 A1 19841122 - WILLING GMBH DR ING [DE]
- [A] DE 740359 C 19431018 - ZEISS IKON A G GOERZ WERK

Cited by

EP1245899A1; EP1045195A3; EP0726420A1; EP0959294A3; WO02063407A1

Designated contracting state (EPC)

AT BE CH DE FR GB IT LI LU NL SE

DOCDB simple family (publication)

EP 0217323 A2 19870408; EP 0217323 A3 19890308

DOCDB simple family (application)

EP 86113329 A 19860927