

Title (en)
BUCKLE, ESPECIALLY FOR A SAFETY BELT IN A MOTOR VEHICLE

Publication
EP 0218517 B1 19890405 (FR)

Application
EP 86402076 A 19860922

Priority
FR 8514290 A 19850926

Abstract (en)
[origin: US4736497A] This buckle is characterized by a device stressing a locking member (5) towards its locking position and a device for ejecting a bolt consist of a first elastic element (20), one end of which intended to interact with the bolt when it is inserted or ejected from the buckle, and the other end of which bears against the first bearing surface of the locking member, and by a device stressing the locking member towards its release position consistent of a second elastic element (21), one end of which bears against the body (4) of the buckle and the other end of which bears against a second bearing surface of the locking member. The first and second bearing surfaces are formed opposite one another on either side of a tongue (13) of the locking member.

IPC 1-7
A44B 11/25

IPC 8 full level
A44B 11/25 (2006.01); **B60R 22/12** (2006.01)

CPC (source: EP US)
A44B 11/2511 (2013.01 - EP US); **Y10T 24/45665** (2015.01 - EP US); **Y10T 24/45717** (2015.01 - EP US)

Designated contracting state (EPC)
DE GB IT SE

DOCDB simple family (publication)
EP 0218517 A1 19870415; EP 0218517 B1 19890405; DE 3662634 D1 19890511; ES 2005830 A6 19890401; FR 2587598 A1 19870327; FR 2587598 B1 19890317; JP S62106704 A 19870518; US 4736497 A 19880412

DOCDB simple family (application)
EP 86402076 A 19860922; DE 3662634 T 19860922; ES 8602447 A 19860925; FR 8514290 A 19850926; JP 22788786 A 19860926; US 91193886 A 19860926