

Title (en)

MIXING DEVICE FOR LIQUIDS

Publication

EP 0219800 A3 19880309 (DE)

Application

EP 86114192 A 19861014

Priority

DE 3536992 A 19851017

Abstract (en)

[origin: EP0219800A2] The device has an inflow line for a first, pressurised liquid as well as at least one suction line for a second liquid, to be mixed in with the first liquid, and an injector in the form of a liquid-jet pump, to the inlet side of which the inflow line is connected, in which a solenoid valve is arranged, and to the suction side of which the suction line is connected, which can be connected to a supply tank for the second liquid. To maintain accurate metering and to prevent a flow back of the mixture, the inflow line is connected to a pressure equalising tank, the liquid level of which is regulated by a liquid pressure switch, controlling the solenoid valve, and the outlet line of which is arranged to flow into the inlet of the injector, with an air gap left inbetween. <IMAGE>

IPC 1-7

C02F 1/68; B01F 3/00; B01F 3/08; G05D 11/13

IPC 8 full level

B01F 3/08 (2006.01); **B01F 5/04** (2006.01); **B01F 15/00** (2006.01)

CPC (source: EP)

B01F 23/40 (2022.01); **B01F 23/49** (2022.01); **B01F 35/2112** (2022.01); **B01F 35/2209** (2022.01); **B01F 25/312** (2022.01)

Citation (search report)

- EP 0143294 A2 19850605 - WEBER & SPRINGMANN [DE]
- US 206427 A 18780730
- US 3376886 A 19680409 - ALFRED KLEIN
- DE 307544 C
- US 3094135 A 19630618 - MARIE PONSAR YVES
- US 4094786 A 19780613 - BURY JOHN R

Cited by

EP0443963A1; EP0465336A1; FR2664179A1; US2014169121A1; US9375688B2

Designated contracting state (EPC)

AT BE CH DE FR GB IT LI LU NL SE

DOCDB simple family (publication)

DE 3536992 C1 19870219; EP 0219800 A2 19870429; EP 0219800 A3 19880309; JP S6415124 A 19890119

DOCDB simple family (application)

DE 3536992 A 19851017; EP 86114192 A 19861014; JP 24562586 A 19861017