

Title (en)

FUEL INJECTION NOZZLE FOR INTERNAL COMBUSTION ENGINES

Publication

**EP 0220207 B1 19880608 (DE)**

Application

**EP 86901817 A 19860326**

Priority

DE 3515723 A 19850502

Abstract (en)

[origin: WO8606441A1] A fuel injection nozzle for internal combustion engines with a valve needle (26) opening outwards and linked with a piston (46) that limits a damping space (62) filled with fuel, which during the opening stroke is connected with the flow-path of the fuel only via a throttle passage. The damping space (62) is formed by a hood (48) inserted over the piston (46). In the base (58) of the hood (48) is a pressure piece (60) actuated by the fuel which presses directly against the piston (46) during the pre-stroke (hv) and then comes to rest on the hood (48). The pressure piece (60) has a smaller diameter than the piston (46) so that the pre-stroke (hv) of the valve needle (26) is more or less damped at least in the lower rpm and loading range.

IPC 1-7

**F02M 61/08; F02M 61/20**

IPC 8 full level

**F02M 61/06** (2006.01); **F02M 61/08** (2006.01); **F02M 61/20** (2006.01)

CPC (source: EP US)

**F02M 61/08** (2013.01 - EP US); **F02M 61/205** (2013.01 - EP US)

Designated contracting state (EPC)

DE FR GB IT

DOCDB simple family (publication)

**WO 8606441 A1 19861106**; DE 3515723 A1 19861106; DE 3660290 D1 19880714; EP 0220207 A1 19870506; EP 0220207 B1 19880608;  
JP S62502699 A 19871015; US 4730785 A 19880315

DOCDB simple family (application)

**DE 8600127 W 19860326**; DE 3515723 A 19850502; DE 3660290 T 19860326; EP 86901817 A 19860326; JP 50182886 A 19860326;  
US 2515186 A 19861205